# SP

Memory is personal

From Ä to C
with Style and Ease

Sharing or More Storage?
It's Up for Both

With its two interfaces, Type-A (USB 3.1 Gen. 1) and Type-C, it is the perfect connection for hassle-free data transmission between any "traditional" USB laptop or PC and new-generation Type-C devices. For fast and convenient data sharing or instant additional storage of up to 128GB for Type-C mobile devices.

Type A

Type C

Swivel-Cap for Allround
Flexibility and Protection

The all-round talent is flexible,
never gets in the way nor lost and always protects the end that is not in use.
And with its classy diamond cut pattern it adds a lot of style to the swivel.

Dual USB Flash Drive
Mobile C31

16GB │ 32GB │ 64GB │ 128GB

Features

· Dual interface Type-A (USB 3.1 Gen 1)/ Type-C flash drive for easy data transmission between Type-A and Type-C port devices
· Instant storage expansion of up to 128GB for Type-C generation mobile devices
· 360° swivel cap for flexible protection and no cap loss
· Metal casing and diamond cut pattern for a classy and modern look
· Tiny and compact
· Protected against water, vibration, and dust through COB technology
· Free download of SP Widget* software (for computer) and SP File Explorer App (for Type-C and Android mobile devices) for efficient file management
· Recuva File Recovery* for data recovery of erased files

*Please download the software from SP Website.

Specifications

· Capacity: 16GB, 32GB, 64GB, 128GB
· Dimension: 33.2 x 12.3 x 8.5mm
· Weight: 3.3g
· Material: Metal, plastic
· Color: Black
· Interface: USB Type-C / USB 3.1 Gen. 1, USB 3.0, USB 2.0 compatible (charging is not supported)
· Supported OS: PC- Windows 10/8.1/8/7/Vista/XP, Mac OS 10.3.x or later, Linux 2.6.x or later, mobile device- Android 4.1.X or later / Windows phone 8 or later
· Operating Temperature: 0℃~70℃
· Certification: CE/FCC/BSMI/KCC/Green dot/WEEE/RoHS
· Warranty: Lifetime warranty

To get more information about supported devices, please go to "Compatibility Search" on the SP website.

CE FC D33B29 RoHS