



100% recycled material used for external cassette



+40% of DYMO® labels are produced\* using „Water based solvents“.



DYMO® high quality labels are made in Belgium



## D1 Standard Polyester Labels

For hundreds of tasks around the office or home office, such as filing, storage and asset tracking.  
Temperature rating: -18°C to 90°C

| D1 STANDARD LABELS (7 m)     | 6 mm     | 9 mm     | 12 mm    | 19 mm    |
|------------------------------|----------|----------|----------|----------|
| ABC                          | S0720780 | S0720680 | S0720530 | S0720830 |
| ABC                          | S0720770 | S0720670 | S0720500 | S0720820 |
| ABC                          | S0720790 | S0720730 | S0720580 | S0720880 |
| ABC                          | -        | S0720710 | S0720560 | S0720860 |
| ABC                          | -        | S0720740 | S0720590 | S0720890 |
| ABC                          | -        | S0720720 | S0720570 | S0720870 |
| ABC                          | -        | -        | S0720610 | S0720910 |
| ABC                          | -        | S0720690 | S0720540 | S0720840 |
| ABC                          | -        | -        | S0720510 | -        |
| ABC                          | -        | -        | S0720600 | -        |
| ABC                          | -        | S0720700 | S0720550 | S0720850 |
| ABC                          | -        | -        | S0720520 | -        |
| D1 STANDARD MULTIPACKS (7 m) | 6 mm     | 9 mm     | 12 mm    | 19 mm    |
| ABC                          | -        | 2093096  | 2093097  | 2093098  |



## D1 Durable Vinyl Labels

Industrial strength adhesive helps to ensure labels stay stuck to a variety of surfaces.  
Temperature rating: -40°C to 80°C

| D1 DURABLE LABELS (3 m)   | 12 mm   |
|---------------------------|---------|
| ABC                       | 1978366 |
| ABC                       | 1978365 |
| ABC                       | 1978367 |
| D1 DURABLE LABELS (5.5 m) | 12 mm   |
| ABC                       | 1978364 |




## D1 Permanent Polyester Labels

Professional, polished finish ideal for panels, blocks, faceplates, shelves, bins and more.  
Temperature rating: -40°C to 150°C\*

| D1 PERMANENT POLYESTER (5.5 m) | 12 mm    | 19 mm    |
|--------------------------------|----------|----------|
| ABC                            | S0718060 | S0718050 |

\*depends on surface



## D1 Flexible Nylon Labels

Specifically designed for curved surfaces and wire and cable marking.  
Temperature rating: -40°C to 60°C

| D1 FLEXIBLE NYLON (3.5 m) | 12 mm    | 19 mm    |
|---------------------------|----------|----------|
| ABC                       | S0718040 | S0718070 |



The DYMO® high quality labels are made in Belgium



© 2021 Newell Brands

This information is being provided for general information purposes and the compliance standards and certifications referenced herein are based on current standards which are subject to change.

