

# ViewSonic LCD DISPLAY

## VX3219-PC-MHD

### Key Features

- 240Hz refresh rate for smooth gameplay
- 1ms (MPRT) response time for precision
- 1500R Curved screen for immersive visuals
- Adaptive™ Sync prevents screen tearing
- Full HD resolution for rich detail



### Product Description

Upgrade your PC experience with the 32" VX3219-PC-MHD. The large display features a 1500R curve for truly immersive gameplay and the ultra-responsive 240Hz display provides pro-level refresh rates, so you can stay ahead of the competition and enjoy ultra-smooth gaming no matter how intense the action gets. A clean design, with 3-side borderless display and sleek dimensions create a product that delivers all you need. Adaptive™ Sync technology virtually eliminates screen tearing and stuttering for a fluid gaming experience. And the 1ms MPRT response time enables you to react in-game with complete precision, removing ghosting and motion blur. VX3219-PC-MHD is also equipped with ViewSonic's exclusive ViewMode™ presets, which offer optimized screen performance for a variety of needs, such as gaming, editing, or watching movies. In addition, a DisplayPort and HDMI inputs offer flexible connectivity for gaming and entertainment.

**Visit Us** — [www.viewsonic.com](http://www.viewsonic.com)

DISPLAY

|                         |   |
|-------------------------|---|
| Display Size (in.):     | 32  |
| Viewable Area (in.):    | 31.5                                      |
| Panel Type:             | VA Technology                             |
| Resolution:             | 1920 x 1080                               |
| Resolution Type:        | FHD                                       |
| Static Contrast Ratio:  | 4,000:1 (typ)                             |
| Dynamic Contrast Ratio: | 80M:1                                     |
| Light Source:           | LED                                       |
| Brightness:             | 300 cd/m² (typ)                           |
| Colors:                 | 16.7M                                     |
| Color Space Support:    | 8 bit (6 bit + FRC)                       |
| Aspect Ratio:           | 16:9                                      |
| Response Time (MPRT):   | 1ms                                       |
| Viewing Angles:         | 178° horizontal, 178° vertical            |
| Backlight Life (Hours): | 30000 Hrs (Min)                           |
| Curvature:              | 1500R                                     |
| Refresh Rate (Hz):      | 240                                       |
| Adaptive Sync:          | Yes                                       |
| Blue Light Filter:      | Yes                                       |
| Flicker-Free:           | Yes                                       |
| Color Gamut:            | NTSC: 72% size (Typ)sRGB: 103% size (Typ) |
| Pixel Size:             | 0.364 mm (H) x 0.364 mm (V)               |
| Surface Treatment:      | Anti-Glare, Hard Coating (3H)             |

COMPATIBILITY

|                        |                                    |
|------------------------|------------------------------------|
| PC Resolution (max):   | 1920x1080                          |
| Mac® Resolution (max): | 1920x1080                          |
| PC Operating System:   | Windows 10 certified; macOS tested |
| Mac® Resolution (min): | 1920x1080                          |

CONNECTOR

|                  |                        |
|------------------|------------------------|
| 3.5mm Audio Out: | 1                      |
| HDMI 2.0:        | 2                      |
| DisplayPort:     | 1                      |
| Power in:        | External power adapter |

AUDIO

|                    |           |
|--------------------|-----------|
| Internal Speakers: | 2Watts x2 |
|--------------------|-----------|

POWER

|                        |                       |
|------------------------|-----------------------|
| Eco Mode (Conserve):   | 25W                   |
| Eco Mode (optimized):  | 31W                   |
| Consumption (typical): | 37W                   |
| Consumption (max):     | 40W                   |
| Voltage:               | AC 100-240V, 50/60 Hz |
| Stand-by:              | 0.5W                  |
| Power Supply:          | External              |

ADDITIONAL HARDWARE

|                       |   |
|-----------------------|---|
| Kensington Lock Slot: | 1 |
|-----------------------|---|

CONTROLS

|                    |   |
|--------------------|---|
| Physical Controls: | Key 1 (favorite), Key 2, Key 3, Key 4, Key 5 (power)                                |
| On Screen Display: | Input Select, Audio Adjust, ViewMode, Color Adjust, Manual Image Adjust, Setup Menu |

OPERATING CONDITIONS

|                            |                             |
|----------------------------|-----------------------------|
| Temperature:               | 32°F to 104°F (0°C to 40°C) |
| Humidity (non-condensing): | 20% to 90%                  |

WALL MOUNT

|                  |              |
|------------------|--------------|
| VESA Compatible: | 100 x 100 mm |
|------------------|--------------|

INPUT SIGNAL

|                       |   |
|-----------------------|---|
| Frequency Horizontal: | HDMI (v2.0): 31.469 ~ 291.309KHz, DisplayPort (v1.2): 31.469 ~ 219.309KHz |
| Frequency Vertical:   | HDMI (v2.0): 48 ~ 240Hz, DisplayPort (v1.2): 48 ~ 240Hz                   |

VIDEO INPUT

|               |  |
|---------------|--|
| Digital Sync: | TMDS - HDMI (v2.0), PCI-E - DisplayPort (v1.2) |
|---------------|--|

ERGONOMICS

|                      |           |
|----------------------|-----------|
| Tilt (Forward/Back): | -5° / 20° |
|----------------------|-----------|

WEIGHT (IMPERIAL)

|                          |      |
|--------------------------|------|
| Net (lbs):               | 10.8 |
| Net Without Stand (lbs): | 9.3  |
| Gross (lbs):             | 15.4 |

WEIGHT (METRIC)

|                         |     |
|-------------------------|-----|
| Net (kg):               | 4.9 |
| Net Without Stand (kg): | 4.2 |
| Gross (kg):             | 7   |

DIMENSIONS (IMPERIAL) (WXHxD)

|                               |                   |
|-------------------------------|-------------------|
| Packaging (in.):              | 38.2 x 20.6 x 6.7 |
| Physical (in.):               | 27.9 x 20.2 x 9   |
| Physical Without Stand (in.): | 27.9 x 16.5 x 3.7 |

DIMENSIONS (METRIC) (WXHxD)

|                              |                 |
|------------------------------|-----------------|
| Packaging (mm):              | 970 x 523 x 170 |
| Physical (mm):               | 709 x 513 x 228 |
| Physical Without Stand (mm): | 709 x 419 x 93  |

GENERAL

|                    |   |
|--------------------|---|
| Regulations:       | cTUVus, FCC-B, ICES003, CEC, NOM, Mexico Energy, CE, CE EMC, CB, RoHS, ErP, REACH, WEEE, EAC, UkrSEPRO, BSMI, RCM, GEMS           |
| PACKAGE CONTENTS:  | VX3219-PC-MHD x1, 3-pin Plug (IEC C13 / CEE22) x1, DisplayPort Cable (v1.2; Male-Male) x1, AC/DC Adapter x1, Quick Start Guide x1 |
| Recycle/Disposal:  | Please dispose of in accordance with local, state or federal laws.  |
| Warranty:          | *Warranty offered may differ from market to market  |
| Country Of Origin: | 28  |