



DATA SHEET

Trusted. Efficient. Versatile.

Exos 10E2400



Seagate® Exos™ 10E2400 enterprise hard drives are the industry's fastest 10K-RPM drives, with capacities up to 2.4 TB in a 2.5-inch form factor, and intended for traditional data centres where density, power consumption and data integrity are paramount.



Best-Fit Applications

- Mission-critical servers and external storage arrays
- Database and online transaction process (OLTP) applications
- Power- and space-constrained data centres
- Green IT and drive-retirement cost reduction initiatives
- Compliance and data security initiatives
- Migration from 3.5 inch drive systems to next-generation technology
- Cost-effective alternative to higher-priced performance solutions



The Perfect Match of High Capacity and High Performance

The high capacity and small 2.5-inch footprint of the Exos 10E2400 drive enables data centres to keep pace with data growth and optimise data centre real estate. Exos 10E2400 delivers up to 2.4 TB of high-performance data access for write-intensive applications. A single advanced format interface model lets you future-proof your storage infrastructure. The Seagate Enhanced Caching feature accelerates read and write I/O operations, preventing applications from slowing down under peak usage conditions. The latest 12 Gb/s SAS interface provides improved scalability.

Maximise Storage Investments for the Long Haul

Exos 10E2400 offers Protection Information (PI) to help protect against data corruption,¹ and Seagate PowerChoice™ technology for T10-compliant power management enables IT organisations to tailor systems for enhanced power consumption. RAID recovery is faster and safer with the help of the Seagate RAID Rebuild® technology option.

Industry-Leading Data Security Features

Seagate Secure™ SED and FIPS 140-2 government-grade models offer hardware-based security to help protect data-at-rest.² With Instant Secure Erase, drive retirement is safe, fast and cost-effective. Seagate Secure models meet the NIST 800-88 media sanitisation specification and support the Trusted Computer Group (TCG) standard.²

Exos 10E300 Enterprise Hard Drives

The industry's fastest 10K-RPM drives are also available in 300 GB capacity and are a perfect choice for entry-level boot server applications.

¹ Protection Information (PI) feature requires PI-compliant host or controller support.

² Seagate Secure models not available in all countries. May require TCG-compliant host or controller support.



| Specifications | FastFormat™ 512 Emulation/4K Native | | | |
|--|-------------------------------------|--------------------|--------------------|--------------------|
| Capacity | 2.4TB | 1.8TB | 1.2TB | 600GB |
| Standard Model | ST2400MM0129 | ST1800MM0129 | ST1200MM0129 | ST600MM0099 |
| Seagate Secure™ SED Model ¹ | — | — | ST1200MM0139 | ST600MM0109 |
| Seagate Secure FIPS 140-2/Common Criteria Model ^{1,2} | ST2400MM0149 | ST1800MM0149 | — | — |
| Performance | | | | |
| Spindle Speed (RPM) | 10,000 RPM | 10,000 RPM | 10,000 RPM | 10,000 RPM |
| Average Latency (ms) | 2.9 | 2.9 | 2.9 | 2.9 |
| Sustained Transfer Rate (Outer to Inner Diameter, MB/s) | 266 to 130 | 266 to 130 | 266 to 130 | 266 to 130 |
| Cache, Multi-segmented (MB) | 256 | 256 | 256 | 256 |
| Enhanced Caching Features | | | | |
| I/O Acceleration and Response Time Optimisation | Enabled | Enabled | Enabled | Enabled |
| NAND Flash Type | eMLC | eMLC | eMLC | eMLC |
| NAND Flash Size | 16 GB | 16 GB | 16 GB | 16 GB |
| Intelligent NAND Endurance Management | Yes | Yes | Yes | Yes |
| Enterprise Features | | | | |
| Secure Download & Diagnostics (SD&D) and Instant Secure Erase Option | Yes | Yes | Yes | Yes |
| FastFormat (512e/4Kn AF Switching) | Yes | Yes | Yes | Yes |
| 12 Gb/s SAS | Yes | Yes | Yes | Yes |
| Configuration/Reliability | | | | |
| Discs/Heads | 4/8 | 3/6 | 2/4 | 1/2 |
| External Transfer Rate (MB/s) | 1,200 | 1,200 | 1,200 | 1,200 |
| Non-recoverable Read Errors per Bits Read, Max | 1 per 10E16 | 1 per 10E16 | 1 per 10E16 | 1 per 10E16 |
| Annualised Failure Rate (AFR) | 0.44% | 0.44% | 0.44% | 0.44% |
| Limited Warranty (years) | 5 | 5 | 5 | 5 |
| Power Management | | | | |
| Typical Op (A) +5V/+12V | 0.47/0.52 | 0.44/0.42 | 0.46/0.41 | 0.46/0.40 |
| Typical Operating (W) | 8.6 | 7.2 | 7.2 | 7.1 |
| Average Idling Power (W) | 4.9 | 4.3 | 3.8 | 3.4 |
| Performance Efficiency Index (Idle W/GB) | 0.0020 | 0.0024 | 0.0032 | 0.0057 |
| Environmental | | | | |
| Ambient Temperature, Operating (°C) | 5°C – 55°C | 5°C – 55°C | 5°C – 55°C | 5°C – 55°C |
| Ambient Temperature, Non-operating (C°) | -40°C – 70°C | -40°C – 70°C | -40°C – 70°C | -40°C – 70°C |
| Shock, Max. Operating: 11ms (Gs) | 40 | 40 | 40 | 40 |
| Shock, Max. Non-operating: 2 ms (Gs) | 400 | 400 | 400 | 400 |
| Vibration, Operating: <500 Hz (Gs) | 0.5 | 0.5 | 0.5 | 0.5 |
| Vibration, Non-operating: <500 Hz (Gs) | 3 | 3 | 3 | 3 |
| Physical | | | | |
| Height (in/mm, max) ³ | 0.591 in/15 mm | 0.591 in/15 mm | 0.591 in/15 mm | 0.591 in/15 mm |
| Width (in/mm, max) ³ | 2.75 in/69.85 mm | 2.75 in/69.85 mm | 2.75 in/69.85 mm | 2.75 in/69.85 mm |
| Depth (in/mm, max) ³ | 3.955 in/100.45 mm | 3.955 in/100.45 mm | 3.955 in/100.45 mm | 3.955 in/100.45 mm |
| Weight (lb/g) | 202 g/0.445 lb | 218 g/0.48 lb | 220 g/0.486 lb | 215 g/0.474 lb |
| Carton Unit Quantity | 40 | 40 | 40 | 40 |
| Cartons per Pallet / Cartons per Layer | 60/10 | 60/10 | 60/10 | 60/10 |

¹ Not all drives may be available in all countries. Seagate Secure drives meet ISO/IEC 27040 and NIST 800-88 standards and may require use of TCG-compliant host or controller support.

² FIPS 140-2 in review. See FIPS 140-2 Level 2 Certificate at <http://csrc.nist.gov/groups/STM/cmvp/validation.html>

³ These base deck dimensions conform to the Small Form Factor Standard (SFF-8201) found at www.sffcommittee.org.



| Specifications | 512 Native | | 512 Native (v8 models) |
|--|--------------------|--------------------|------------------------|
| Capacity | 1.2TB | 600GB | 300GB |
| Standard Model | ST1200MM0009 | ST600MM0009 | ST300MM0048 |
| Seagate Secure™ SED Model ¹ | ST1200MM0039 | ST600MM0039 | ST300MM0058 |
| Seagate Secure FIPS 140-2/Common Criteria Model ^{1,2} | — | — | — |
| Performance | | | |
| Spindle Speed (RPM) | 10,000 RPM | 10,000 RPM | 10,000 RPM |
| Average Latency (ms) | 2.9 | 2.9 | 2.9 |
| Sustained Transfer Rate (Outer to Inner Diameter, MB/s) | 250 to 130 | 250 to 130 | 215 to 125 |
| Cache, Multi-segmented (MB) | 128 | 128 | 128 |
| Enhanced Caching Features | | | |
| I/O Acceleration and Response Time Optimisation | — | — | — |
| NAND Flash Type | — | — | — |
| NAND Flash Size | — | — | — |
| Intelligent NAND Endurance Management | — | — | — |
| Enterprise Features | | | |
| Secure Download & Diagnostics (SD&D) and Instant Secure Erase Option | Yes | Yes | Yes |
| FastFormat (512e/4Kn AF Switching) | — | — | — |
| 12 Gb/s SAS | Yes | Yes | Yes |
| Configuration/Reliability | | | |
| Discs/Heads | 2/4 | 1/2 | 1/2 |
| External Transfer Rate (MB/s) | 1,200 | 1,200 | 1,200 |
| Non-recoverable Read Errors per Bits Read, Max | 1 per 10E16 | 1 per 10E16 | 1 per 10E16 |
| Annualised Failure Rate (AFR) | 0.44% | 0.44% | 0.44% |
| Limited Warranty (years) | 5 | 5 | 5 |
| Power Management | | | |
| Typical Op (A) +5V/+12V | 0.46/0.41 | 0.46/0.40 | 0.46/0.40 |
| Typical Operating (W) | 7.2 | 7.1 | 6.3 |
| Average Idling Power (W) | 3.8 | 3.4 | 3.4 |
| Performance Efficiency Index (Idle W/GB) | 0.0032 | 0.0057 | 0.0057 |
| Environmental | | | |
| Ambient Temperature, Operating (°C) | 5°C – 55°C | 5°C – 55°C | 5°C – 55°C |
| Ambient Temperature, Non-operating (C°) | -40°C – 70°C | -40°C – 70°C | -40°C – 70°C |
| Shock, Max. Operating: 11ms (Gs) | 40 | 40 | 40 |
| Shock, Max. Non-operating: 2 ms (Gs) | 400 | 400 | 400 |
| Vibration, Operating: <500 Hz (Gs) | 0.5 | 0.5 | 0.5 |
| Vibration, Non-operating: <500 Hz (Gs) | 3 | 3 | 3 |
| Physical | | | |
| Height (in/mm, max) ³ | 0.591 in/15 mm | 0.591 in/15 mm | 0.591 in/15 mm |
| Width (in/mm, max) ³ | 2.76 in/70.1 mm | 2.76 in/70.1 mm | 2.76 in/70.1 mm |
| Depth (in/mm, max) ³ | 3.955 in/100.45 mm | 3.955 in/100.45 mm | 3.955 in/100.45 mm |
| Weight (lb/g) | 220 g/0.486 lb | 215 g/0.474 lb | 215 g/0.474 lb |
| Carton Unit Quantity | 40 | 40 | 40 |
| Cartons per Pallet / Cartons per Layer | 60/10 | 60/10 | 60/10 |

1 Not all drives may be available in all countries. Seagate Secure drives meet ISO/IEC 27040 and NIST 800-88 standards and may require use of TCG-compliant host or controller support.

2 FIPS 140-2 in review. See FIPS 140-2 Level 2 Certificate at <http://csrc.nist.gov/groups/STM/cmvp/validation.html>

3 These base deck dimensions conform to the Small Form Factor Standard (SFF-8201) found at www.sffcommittee.org.

seagate.com



AMERICAS Seagate Technology LLC 10200 South De Anza Boulevard, Cupertino, California 95014, United States, 408-658-1000
ASIA/PACIFIC Seagate Singapore International Headquarters Pte. Ltd. 7000 Ang Mo Kio Avenue 5, Singapore 569877, 65-6485-3888
EUROPE, MIDDLE EAST, AND AFRICA Seagate Technology SAS 16-18, rue du Dôme, 92100 Boulogne-Billancourt, France, 33 1-4186 10 00