



# Rhino™ 6000+

**PC-connected or portable labeling tool that saves you time and money**  
It's packed with time-saving shortcuts for labeling any installation quickly and professionally.

- Create labels up to 24mm width
- Transfer files including barcodes from Dymo ID™ software\* on PC to the Rhino 6000+ for easy editing on the job
- Meets key ANSI and TIA/EIA-606-B industry labeling standards
- Exclusive, one-touch "Hot Keys" automatically size, space and format label text for electrical and patch panels, terminal and 110 blocks, wire and cable flags, horizontal and vertical wraps, vertical and fixed-length applications including 5-line print capability
- Print 8 barcode types including Code 39, Code 128, Codabar, UPC A/E, EAN 8/13, PDF 417, code 39 mod 43 variant and QR code
- Symbol library includes more than 250 pre-programmed industry symbols, terms, fractions and punctuation marks
- Always use authentic Dymo® Industrial Rhino™ labels for guaranteed high-quality output
- For more features download the free Dymo ID™ software for PC and use it to create labels even faster

\* Works with 32- and 64-bit Windows® 7 or later.



DYMO ID



No ink or toner required



REACH compliant



RoHS compliant



Bring the tough, portable Rhino™ 6000+ to any jobsite

## Single Kit includes:

- Rhino 6000+ Printer
- Industrial Rhino white Vinyl 9 mm and Flexible Nylon 24 mm tapes
- Rechargeable Battery Pack
- AC Adapter
- USB cable
- Carry Case
- Quick start guide



### Quick Specs

|                             |                            |
|-----------------------------|----------------------------|
| Unit Dimensions (H x W x L) | 75 x 137.16 x 246.38 mm    |
| Weight (excluding battery)  | 1.81 kg                    |
| Mac®/PC Compatible          | PC only                    |
| Accepts Label Sizes         | 6mm, 9mm, 12mm, 19mm, 24mm |
| Tape Platform               | IND                        |
| Resolution                  | 180 dpi                    |
| Printing System             | Thermal Transfer           |
| Print Speed                 | 10.16 mm/sec               |
| Barcodes                    | Yes                        |
| Cutter Type                 | Electronic                 |
| Batteries                   | Rechargeable (included)    |
| AC Adapter                  | Yes (included)             |
| Networking                  | No                         |
| Country of Origin           | China                      |

| Item Number | Description              | Unit | Length (cm) | Width (cm) | Height (cm) | Weight (kg) | QTY | EAN           | Customer Price |
|-------------|--------------------------|------|-------------|------------|-------------|-------------|-----|---------------|----------------|
| 2122967     | RH6000+ ABC 24MM CASE UK | Unit | 45.0        | 10.2       | 34.9        | 6.9         | 1   | 3026981229671 |                |



100% recycled material used  
for external cassette



Reach  
compliant



RoHS  
compliant



DYMO® high quality labels  
are made in Belgium

#### IND Vinyl

Ideal for both indoor and outdoor applications. Available in the widest range of colors that meet OSHA, ANSI and ISO color standards.

- UL recognized component to UL 969
- REACH / RoHS compliant
- Temperature rating: -40°C to 80°C

#### IND Flexible Nylon

Specifically designed for curved surfaces and wire and cable marking.

- UL recognized component to UL 969
- REACH / RoHS compliant
- Temperature rating: -10°C to 80°C
- Authentic DYMO® labels are made in Belgium, Europe

#### IND Permanent Polyester

Professional, polished finish ideal for panels, blocks, faceplates, shelves, bins, beams and more.





- UL recognized component to UL 969
- REACH / RoHS compliant
- For flat surfaces only
- Temperature rating: -40°C to 150°C

#### IND Heat-Shrink Tube

For high-end cable identification. A 3:1 shrink ratio helps ensure a secure fit on wires and cables.

- Meets MIL-M-81531, MIL-STD-202G, SAE-DTL-23053/5 (Class 1 & 3)
- UL recognized as a component to UL 224
- REACH / RoHS compliant
- Temperature rating: -55°C to 135°C

### Rhino™ Industrial Labels

|                         | Length | 6mm     | 9mm      | 12mm    | 19mm    | 24mm    |   |
|-------------------------|--------|---------|----------|---------|---------|---------|---|
| IND VINYL               |        |         |          |         |         |         |   |
| A                       | 5.5m   | -       | 18443    | 18444   | 18445   | 1805430 |  |
| A                       |        | -       | -        | 18432   | 18433   | 1805431 |   |
| A                       |        | -       | -        | 18435   | 18436   | 18436   |   |
| A                       |        | -       | -        | 1805416 | -       | -       |   |
| A                       |        | -       | 1805437  | 1805435 | 1805436 | 1805432 |   |
| A                       |        | -       | -        | 1805414 | 1805420 | -       |   |
| A                       |        | -       | -        | 1805243 | 1805417 | -       |   |
| A                       |        | -       | -        | -       | 1805422 | -       |   |
| IND PERMANENT POLYESTER |        |         |          |         |         |         |   |
| A                       | 5.5m   | 1805442 | 18482    | 18483   | 18484   | 1734523 |  |
| A                       |        | -       | 18508DMO | 622289  | 622290  | -       |   |
| A                       |        | 1805441 | 18485    | 18486   | 18487   | -       |   |
| IND FLEXIBLE NYLON      |        |         |          |         |         |         |   |
| A                       | 3.5m   | -       | -        | 18488   | 18489   | 1734524 |  |
| A                       |        | -       | -        | 18490   | 18491   | 1734525 |   |
| IND HEAT-SHRINK TUBE    |        |         |          |         |         |         |   |
| A                       | 1.5m   | 18051   | 18053    | 18055   | 18057   | 1805443 |  |
| A                       |        | 18052   | 18054    | 18056   | 18058   | 1805444 |   |

Country of Origin: Belgium

**DYMO**

**newell**  
BRANDS

© 2021 Newell Brands

This information is being provided for general information purposes and the compliance standards and certifications referenced herein are based on current standards which are subject to change.

Microsoft and Windows are either registered trademarks or trademarks of Microsoft Corporation in the United States and/or other countries.

