

# ProSAFE® M4300 Intelligent Edge Series

Mixed stacking and full PoE+ provision



## M4300 series

The ProSAFE® M4300 Stackable L3 Managed Switch Series comes with 10G and 1G models in a variety of form factors and PoE+ full provisioning. SDN-ready with OpenFlow 1.3, M4300 Switch Series delivers IPv4/IPv6 rich services for mid-enterprise edge and SMB core with mixed stacking between 10 Gigabit and 1 Gigabit models. Layer 3 feature set includes static and policy-based routing, RIP, VRRP, OSPF, and PIM dynamic routing. M4300 is ideal for server aggregation with Auto-iSCSI prioritization, wireless access, unified communications and IP video.



## Building 1


- For midsize server installations, two half-width M4300 10GbE models can be paired in a single rack space for redundant top-of-rack
- Compared with single top-of-rack switch installation, such two-unit horizontal stacking is cost-effective yet highly efficient for HA
- Management unit hitless failover and nonstop forwarding ensure no single point of failure for servers and storage

## Building 2

- Common for intermediate distribution frames (IDF) in K-12 and other large campuses, stacking topologies greatly simplify deployments at the edge
- While reducing the number of logical units to manage, stacking also brings network resiliency with distributed uplinks in aggregation to the core
- Management unit hitless failover and nonstop forwarding ensures continuous uptime for clients across the stack

## Building 3

- For typical collapsed core installations, with a variety of 1G and 10G access ports in branch offices, server rooms or campus high performance labs
- M4300 10G models can stack with M4300 1G models, enabling innovative "spine and leaf" topologies
- Spine and leaf architectures deliver highest performance with every leaf switch (1G) connecting to every spine switch (10G) for a fully non-blocking deployment
- With management unit hitless failover and nonstop forwarding, leaf switches keep forwarding L2 and L3 traffic in and out, while backup spine unit guarantees connectivity to the core



## M4300 Series Features

ProSAFE® M4300 Stackable L3 Managed Switch Series comes with 10G and 1 G models in a variety of form factors and PoE+ full provisioning. SDN-ready with OpenFlow 1.3, M4300 Switch Series delivers IPv4/IPv6 rich services for mid-enterprise edge and SMB core with mixed stacking between 10 Gigabit and 1 Gigabit models. Layer 3 feature set includes static and policy-based routing, RIP, VRRP, OSPF, and Multicast PIM dynamic routing. M4300 is ideal for server aggregation with Auto-iSCSI prioritization, wireless access, unified communications and IP video.

### NETGEAR M4300 series key features:

- Cost effective 1G access layer in campus LAN networks, and high performance 10G distribution layer for midsize organizations networks
- Advanced Layer 2, Layer 3 and Layer 4 feature set – no license required – including Policy Based Routing, RIP, VRRP, OSPF and PIM
- Innovative mixed “Spine and Leaf”, 1G and 10G stacking with nonstop forwarding and hitless failover redundancy
- Low acoustics, half-width 16-port and 24-port 10G models can be paired in a single rack space for redundant Top of Rack
- Up to 384 (Gigabit) ports, or 384 (10 Gigabit) ports, or a combination of both in a single logical switch
- PoE+ (30 watts per port) with hot swap, redundant power supplies and full provisioning
- 48-port 10G models ultra-low latency and scalable table size with 128K MAC, 8K ARP/NDP, 4K VLANs, 12K routes
- Mixed Stack of 1G and 10G models provides 16K MAC, 2K ARP/NDP, 4K VLANs and 512 routes
- SDN-Ready OpenFlow 1.3 support for maximum investment protection

### NETGEAR M4300 series software features:

- Advanced classifier-based, time-based hardware implementation for L2 (MAC), L3 (IP) and L4 (UDP/TCP transport ports) security and prioritization
- Selectable Port-Channel / LAG (802.3ad – 802.1AX) L2/L3/L4 hashing for fault tolerance and load sharing with any type of Ethernet channeling
- Voice VLAN with SIP, H323 and SCCP protocols detection and LLDP-MED IP phones automatic QoS and VLAN configuration
- Efficient authentication tiering with successive DOT1X, MAB and Captive Portal methods for streamlined BYOD
- Comprehensive IPv4/IPv6 static and dynamic routing including Proxy ARP, OSPF, Policy-based routing and automatic 6-to-4 tunneling
- Enhanced IPv4/IPv6 multicast forwarding with IGMPv3/MLDv2 ASM and SSM Proxy and Control Packet Flooding protection
- High performance IPv4/IPv6 multicast routing with PIM timer accuracy and unhandled PIM (S,G,rpt) state machine events transitioning
- Advanced IPv4/IPv6 security implementation including malicious code detection, DHCP Snooping, IP Source Guard protection and DoS attacks mitigation
- Innovative multi-vendor Auto-iSCSI capabilities for easier virtualization optimization

### NETGEAR M4300 series resiliency and availability features:

- Dual redundant, modular power supplies equipping full width models contribute to business continuity management
- Vertical or horizontal flexible stacking with management unit hitless failover and nonstop forwarding across operational stack members
- Spine and leaf architecture with every leaf switch (1G access switches) connecting to every spine switch (distributed 10G “core” switches)
- Stacking and distributed link aggregation allow for multi-resiliency with zero downtime and load balancing capabilities
- Link Dependency new feature enables or disables ports based on the link state of different ports
- Per VLAN Spanning Tree and Per VLAN Rapid Spanning Tree (PVSTP/PVRSTP) offer interoperability with PVST+ infrastructures

### NETGEAR M4300 series management features:

- DHCP/BootP innovative auto-installation including firmware and configuration file upload automation
- Industry standard SNMP, RMON, MIB, LLDP, AAA, sFlow and RSPAN remote mirroring implementation
- Service port for out-of-band Ethernet management (OOB)
- Standard RS232 straight-through serial RJ45 and Mini-USB ports for local management console
- Standard USB port for local storage, logs, configuration or image files
- Dual firmware image and configuration file for updates with minimum service interruption
- Industry standard command line interface (CLI) for IT admins used to other vendors commands
- Fully functional Web console (GUI) for IT admins who prefer an easy to use graphical interface
- Single-pane-of-glass NMS300 management platform with mass-configuration support

### NETGEAR M4300 series warranty and support:

- NETGEAR ProSAFE Lifetime Hardware Warranty\*
- Included Lifetime Technical Support
- Included Lifetime Next Business Day Hardware Replacement

## Hardware at a Glance

			FRONT		REAR		MANAGEMENT	
10G models Model name	Form-Factor	Switching Fabric	100/1000/10GBASE-T RJ45 ports	1000/10GBASE-X SFP+ ports	PSU	Fans	Out-of-band Console	Model number
<b>M4300-8X8F</b>	Half-width 1-unit 1U 2-unit 1U rack mount	320 Gps	<b>8 ports</b> (independent) 100M; 1G; 10G	<b>8 ports</b> (independent) 1G; 10G	<b>Modular 1 bay</b> 1 PSU included: APS250W	<b>Fixed</b> Front-to-back 36.9dB	Ethernet: Out-of-band 1G port (Front)Console: RJ45 RS232 (Front) Console: Mini-USB (Front) Storage: USB (Front)	<b>XSM4316S</b>
<b>M4300-12X12F</b>	Half-width 1-unit 1U 2-unit 1U rack mount	480 Gps	<b>12 ports</b> (independent) 100M; 1G; 10G	<b>12 ports</b> (independent) 1G; 10G	<b>Modular 1 bay</b> 1 PSU included: APS250W	<b>Fixed</b> Front-to-back 36.9dB	Ethernet: Out-of-band 1G port (Back)Console: RJ45 RS232 (Back) Console: Mini-USB (Front) Storage: USB (Front)	<b>XSM4324S</b>
<b>M4300-24X</b>	Half-width 1-unit 1U 2-unit 1U rack mount	480 Gps	<b>24 ports</b> 100M; 1G; 10G	<b>4 ports</b> (shared, back) 1G; 10G	<b>Modular 1 bay</b> 1 PSU included: APS250W	<b>Fixed</b> Front-to-back 37dB	Ethernet: Out-of-band 1G port (Back)Console: RJ45 RS232 (Back) Console: Mini-USB (Front) Storage: USB (Front)	<b>XSM4324CS</b>
<b>M4300-24X24F</b>	Full width 1-unit 1U rack mount	960 Gps	<b>24 ports</b> (independent) 100M; 1G; 10G	<b>24 ports</b> (independent) 1G; 10G	<b>Modular 2 bays</b> 1 PSU included: APS250W	<b>Fixed</b> Front-to-back 35.8dB	Ethernet: Out-of-band 1G port (Front)Console: RJ45 RS232 (Front) Console: Mini-USB (Front) Storage: USB (Front)	<b>XSM4348S</b>
<b>M4300-48X</b>	Full width 1-unit 1U rack mount	960 Gps	<b>48 ports</b> 100M; 1G; 10G	<b>4 ports</b> (shared) 1G; 10G	<b>Modular 2 bays</b> 1 PSU included: APS250W	<b>Fixed</b> Front-to-back 40.3dB	Ethernet: Out-of-band 1G port (Back)Console: RJ45 RS232 (Back) Console: Mini-USB (Front) Storage: USB (Front)	<b>XSM4348CS</b>

### Rear View



M4300-24X  
M4300-48X  
M4300-8X8F  
M4300-12X12F  
M4300-24X24F  
M4300-28G  
M4300-52G  
M4300-28G-PoE+  
M4300-52G-PoE+

### Front View



## Hardware at a Glance

			FRONT			REAR		MANAGEMENT	
1G models Model name	Form-Factor	Switching Fabric	10/100/1000 BASE-T RJ45 ports	100/1000/10G BASE-T RJ45 ports	1000/10G BASE-X SFP+ ports	PSU	Fans	Out-of-band Console	Model number
<b>M4300-28G</b>	<b>Full width</b> 1-unit 1U rack mount	128 Gps	<b>24 ports</b>	<b>2 ports</b> (independent) 100M; 1G; 10G	<b>2 ports</b> (independent) 1G; 10G	<b>Modular 2 bays</b> 1 PSU included: APS150W	<b>Fixed</b> Front-to-back 30.3dB	Ethernet: Out-of-band 1G port (Front)Console: RJ45 RS232 (Back) Console: Mini-USB (Front) Storage: USB (Front)	<b>GSM4328S</b>
<b>M4300-52G</b>	<b>Full width</b> 1-unit 1U rack mount	176 Gps	<b>48 ports</b>	<b>2 ports</b> (independent) 100M; 1G; 10G	<b>2 ports</b> (independent) 1G; 10G	<b>Modular 2 bays</b> 1 PSU included: APS150W	<b>Fixed</b> Front-to-back 31.5dB	Ethernet: Out-of-band 1G port (Front)Console: RJ45 RS232 (Back) Console: Mini-USB (Front) Storage: USB (Front)	<b>GSM4352S</b>
<b>M4300-28G-PoE+</b>	<b>Full width</b> 1-unit 1U rack mount	128 Gps	<b>24 ports PoE+</b>	<b>2 ports</b> (independent) 100M; 1G; 10G	<b>2 ports</b> (independent) 1G; 10G	<b>Modular 2 bays</b> 1 PSU included: APS550W	<b>Fixed</b> Front-to-back 39.8dB	Ethernet: Out-of-band 1G port (Front)Console: RJ45 RS232 (Back) Console: Mini-USB (Front) Storage: USB (Front)	<b>GSM4328PA</b>
			110V/220V AC input 480W PoE Budget with 1 PSU 480W PoE Budget with 2 PSUs in RPS mode 720W PoE Budget with 2 PSUs in EPS mode	480W PoE Budget with 1 PSU 630W PoE Budget with 2 PSUs in RPS mode 720W PoE Budget with 2 PSUs in EPS mode		1 PSU included: APS1000W			<b>GSM4328PB</b>
<b>M4300-52G-PoE+</b>	<b>Full width</b> 1-unit 1U rack mount	176 Gps	<b>48 ports PoE+</b>	<b>2 ports</b> (independent) 100M; 1G; 10G	<b>2 ports</b> (independent) 1G; 10G	<b>Modular 2 bays</b> RPS connector 1 PSU included: APS550W	<b>Fixed</b> Front-to-back 39.8dB	Ethernet: Out-of-band 1G port (Front)Console: RJ45 RS232 (Back) Console: Mini-USB (Front) Storage: USB (Front)	<b>GSM4352PA</b>
			110V/220V AC input 480W PoE Budget with 1 PSU 480W PoE Budget with 2 PSUs in RPS mode 720W PoE Budget with 2 PSUs in EPS mode	591W PoE Budget with 1 PSU 591W PoE Budget with 2 PSUs in RPS mode 1,010W PoE Budget with 2 PSUs in EPS mode		1 PSU included: APS1000W	External RPS4000 for power redundancy (RPS) when 2 internal PSUs are used in EPS mode		<b>GSM4352PB</b>
			110V AC input 591W PoE Budget with 1 PSU 591W PoE Budget with 2 PSUs in RPS mode 1,010W PoE Budget with 2 PSUs in EPS mode	860W PoE Budget with 1 PSU 860W PoE Budget with 2 PSUs in RPS mode 1,440W PoE Budget with 2 PSUs in EPS mode			External RPS4000 for power redundancy (RPS) when 2 internal PSUs are used in EPS mode		

PoE models: APS550W and APS1000W cannot be mixed and matched. A switch can only have two APS550W, or two APS1000W. PA versions can be upgraded to PB, but their APS550W must be replaced by APS1000W (and reversely).

## Software at a Glance

	LAYER 3 PACKAGE											
Model name	Management	Usability Enhancements	IPv4/IPv6 ACL and QoS, DiffServ	IPv4/IPv6 Multicast filtering	IPv4 / IPv6 Policing and Convergence	Spanning Tree Green Ethernet	VLANs	Trunking Port Channel	IPv4/IPv6 Authentication Security	IPv4/IPv6 Static Routing	IPv4/IPv6 Dynamic Routing	Model number
<b>M4300 series</b>	Out-of-band; Web GUI; HTTPS; CLI; Telnet; SSH  SNMP, MIBs RSPAN  Radius Users, TACACS+	Stacking NSF with Hitless Failover  Link Dependency (Enable or Disable one or more ports based on the link state of one or more different ports)  Syslog and Packet Captures can be sent to USB storage	Ingress/egress  1 Kbps shaping Time-based  Single Rate Policing	IGMPv3 MLDv2 Snooping, Proxy ASM & SSM  IGMPv1,v2 Querier  Control Packet Flooding	Auto-VoIP  Auto-iSCSI  Policy-based routing (PBR)  LLDP-MED	STP, MTP, RSTP  PV(R)STP <sup>1</sup>  BPDU/STRG Root Guard  EEE <sup>2</sup> (802.3az)	Static, Dynamic,  Voice, MAC  GVRP/GMRP  QinQ,  Private VLANs	Distributed LAG across the stack  Static or Dynamic LACP  Seven (7) L2/L3/L4 hashing algorithms	Successive Tiering  (DOT1X; MAB; Captive Portal)  DHCP Snooping Dynamic ARP Inspection IP Source Guard	Port, Subnet, VLAN routing, DHCP Relay;  Multicast static routes;  Stateful DHCPv6 Server	IPv4: RIP, VRRP  IPv4/IPv6: OSPF, Proxy ARP, PIM-SM, PIM-DM, 6-to-4 tunnels	<b>All models</b>

<sup>1</sup> CLI only

<sup>2</sup> Future firmware upgrade

## Performance at a Glance

	TABLE SIZE*												
Model name	MAC ARP/NDP	Routing / Switching Capacity	Throughput	Application Route Scaling	Packet Buffer	Latency	IP Multicast Forwarding Entries	Multicast IGMP Group membership	CPU	VLANs	DHCP	sFlow	Model number
<b>M4300-24X24F</b> <b>M4300-48X</b>	128K MAC  8K ARP/NDP	960 Gbps  Line-rate	714 Mpps	Static: 64v4/ 64v6  RIP: 512  OSPF: 12,000	56Mb	64-byte  M4300-24X24F <2.39µs 10G RJ45 <0.88µs 10G SFP+  M4300-48X <2.41µs 10G RJ45 <1.51µs 10G SFP+	1,024 IPv4  512 IPv6	2K IPv4  2K IPv6	CPU 800 Mhz  1GB RAM  256MB Flash	4K VLANs	DHCP Server: 2K leases  IPv4: 256 pools  IPv6: 16 pools	416 samplers  416 pollers  8 receivers	<b>XSM4348S</b> <b>XSM4348CS</b>
<b>M4300 other models</b>	16K MAC  2K ARP/NDP	Up to 480 Gbps  All models Line-rate	Up to 357 Mpps	Static: 64v4/ 64v6  RIP: 512  OSPF: 512	M4300-12X12F: 32Mb  Others: 16Mb	M4300-8X8F: <2.43µs 10G RJ45 <0.89µs 10G SFP+  All others: <2.76µs 10G RJ45 <1.83µs 10G SFP+	96 IPv4  32 IPv6						<b>All other models</b>

For mixed stacking between more capable devices and less capable devices, SDM mixed stacking template is used based on "least common denominator" set of capacities and capabilities

## Components

### M4300-8X8F Stackable Managed Switch


#### Ordering information

- Americas, Europe: XSM4316S-100NES
- Asia Pacific: XSM4316S-100AJS
- Warranty: Lifetime ProSafe Hardware Warranty



- 8-port 10GBASE-T (RJ45) all independent
- 8-port 10GBASE-X (SFP+) all independent
- 320Gbps non-blocking fabric across 16 ports
- Out-of-band 1G Ethernet management port
- Mini-USB and RJ45 RS232 console ports and USB storage port
- Full L3 feature set and non-stop forwarding (NSF) stacking
- Half-width form factor with one- and two-unit rack mount kit
- Two half-width switches can be installed in a single rack space for redundant top-of-rack
- Ships with one modular APS250W PSU in its power supply slot
- Low acoustics (36.9dB @25°C / 77°F)

To install a single half-width switch in a rack, a 19-inch rack-mount kit is supplied with the switch:



To install two half-width switches in a rack, inside and outside middle mounts and rack-mount brackets are supplied with the switches:



## Components

### M4300-12X12F Stackable Managed Switch

#### Ordering information

- Americas, Europe: XSM4324S-100NES
- Asia Pacific: XSM4324S-100AJS
- Warranty: Lifetime ProSAFE Hardware Warranty



- 12-port 10GBASE-T (RJ45) all independent
- 12-port 10GBASE-X (SFP+) all independent
- 480Gbps non-blocking fabric across 24 ports
- Out-of-band 1G Ethernet management port
- Mini-USB and RJ45 RS232 console ports and USB storage port
- Full L3 feature set and non-stop forwarding (NSF) stacking
- Half-width form factor with one- and two-unit rack mount kit
- Two half-width switches can be installed in a single rack space for redundant top-of-rack
- Ships with one modular APS250W PSU in its power supply slot
- Low acoustics (36.9dB @25°C / 77°F)



### M4300-24X Stackable Managed Switch

#### Ordering information

- Americas, Europe: XSM4324CS-100NES
- Asia Pacific: XSM4324CS-100AJS
- Warranty: Lifetime ProSAFE Hardware Warranty



- 24-port 10GBASE-T (RJ45)
- 4-port 10GBASE-X (SFP+) (shared, back)
- 480Gbps non-blocking fabric across 24 ports
- Out-of-band 1G Ethernet management port
- Mini-USB and RJ45 RS232 console ports and USB storage port
- Full L3 feature set and non-stop forwarding (NSF) stacking
- Half-width form factor with one- and two-unit rack mount kit
- Two half-width switches can be installed in a single rack space for redundant top-of-rack
- Ships with one modular APS250W PSU in its power supply slot
- Low acoustics (37dB @25°C / 77°F)





## Components


### M4300-24X24F Stackable Managed Switch

#### Ordering information

- Americas, Europe: XSM4348S-100NES
- Asia Pacific: XSM4348S-100AJS
- Warranty: Lifetime ProSAFE Hardware Warranty



- 24-port 10GBASE-T (RJ45) all independent
- 24-port 10GBASE-X (SFP+) all independent
- 960Gbps non-blocking fabric across 48 ports
- Out-of-band 1G Ethernet Management port
- Mini-USB and RJ45 RS232 console ports and USB storage port
- Full L3 feature set and non-stop forwarding (NSF) stacking
- Full width form factor with one-unit rack mount kit
- Ships with one modular APS250W PSU in first power supply slot
- Ship with a blank cover in the second power supply slot
- Low acoustics (35.8dB @25°C / 77°F)




### M4300-48X Stackable Managed Switch

#### Ordering information

- Americas, Europe: XSM4348CS-100NES
- Asia Pacific: XSM4348CS-100AJS
- Warranty: Lifetime ProSAFE Hardware Warranty



- 48-port 10GBASE-T (RJ45)
- 4-port 10GBASE-X (SFP+) (shared)
- 960Gbps non-blocking fabric across 48 ports
- Out-of-band 1G Ethernet Management port
- Mini-USB and RJ45 RS232 console ports and USB storage port
- Full L3 feature set and non-stop forwarding (NSF) stacking
- Full width form factor with one-unit rack mount kit
- Ships with one modular APS250W PSU in first power supply slot
- Ship with a blank cover in the second power supply slot
- Low acoustics (40.3dB @25°C / 77°F)



## Components

### M4300-28G Stackable Managed Switch

#### Ordering information

- Americas, Europe: GSM4328S-100NES
- Asia Pacific: GSM4328S-100AJS
- Warranty: Lifetime ProSAFE Hardware Warranty



- 24-port 1000BASE-T (RJ45)
- 2-port 10GBASE-T (RJ45) all independent
- 2-port 10GBASE-X (SFP+) all independent
- 128Gbps non-blocking fabric across 28 ports
- Out-of-band 1G Ethernet Management port
- Mini-USB and RJ45 RS232 console ports and USB storage port
- Full L3 feature set and non-stop forwarding (NSF) stacking
- Full width form factor with one-unit rack mount kit
- Ships with one modular APS150W PSU in first power supply slot
- Ship with a blank cover in the second power supply slot
- Low acoustics (30.3dB @25°C / 77°F)




### M4300-52G Stackable Managed Switch

#### Ordering information

- Americas, Europe: GSM4352S-100NES
- Asia Pacific: GSM4352S-100AJS
- Warranty: Lifetime ProSafe Hardware Warranty



- 48-port 1000BASE-T (RJ45)
- 2-port 10GBASE-T (RJ45) all independent
- 2-port 10GBASE-X (SFP+) all independent
- 176Gbps non-blocking fabric across 52 ports
- Out-of-band 1G Ethernet Management port
- Mini-USB and RJ45 RS232 console ports and USB storage port
- Full L3 feature set and non-stop forwarding (NSF) stacking
- Full width form factor with one-unit rack mount kit
- Ships with one modular APS150W PSU in first power supply slot
- Ship with a blank cover in the second power supply slot
- Low acoustics (31.5dB @25°C / 77°F)



## Components


### M4300-28G-PoE+ Stackable Managed Switch

#### Ordering information

- Americas, Europe (550W PSU): GSM4328PA-100NES
- Americas, Europe (1,000W PSU): GSM4328PB-100NES
- Asia Pacific (550W PSU): GSM4328PA-100AJS
- Asia Pacific (1,000W PSU): GSM4328PB-100AJS
- Warranty: Lifetime ProSAFE Hardware Warranty



- 24-port 1000BASE-T (RJ45) PoE+
- 2-port 10GBASE-T (RJ45) all independent
- 2-port 10GBASE-X (SFP+) all independent
- 128Gbps non-blocking fabric across 28 ports
- Out-of-band 1G Ethernet Management port
- Mini-USB and RJ45 RS232 console ports and USB storage port
- Full L3 feature set and non-stop forwarding (NSF) stacking
- Full width form factor with one-unit rack mount kit
- (GSM4328PA) Ships with one modular APS550W PSU in first power supply slot
- (GSM4328PB) Ships with one modular APS1000W PSU in first power supply slot
- Ship with a blank cover in the second power supply slot




### M4300-52G-PoE+ Stackable Managed Switch

#### Ordering information

- Americas, Europe (550W PSU): GSM4352PA-100NES
- Americas, Europe (1,000W PSU): GSM4352PB-100NES
- Asia Pacific (550W PSU): GSM4352PA-100AJS
- Asia Pacific (1,000W PSU): GSM4352PB-100AJS
- Warranty: Lifetime ProSAFE Hardware Warranty



- 48-port 1000BASE-T (RJ45) PoE+
- 2-port 10GBASE-T (RJ45) all independent
- 2-port 10GBASE-X (SFP+) all independent
- 176Gbps non-blocking fabric across 52 ports
- Out-of-band 1G Ethernet Management port
- Mini-USB and RJ45 RS232 console ports and USB storage port
- Full L3 feature set and non-stop forwarding (NSF) stacking
- Full width form factor with one-unit rack mount kit
- (GSM4352PA) Ships with one modular APS550W PSU in first power supply slot
- (GSM4352PB) Ships with one modular APS1000W PSU in first power supply slot
- Ship with a blank cover in the second power supply slot




Components

RPS4000v2  
RPS unit for up to 4 concurrent switches

- Ordering information
- Americas, Europe: RPS4000-200NES
  - Asia Pacific: RPS4000-200AJS
  - Warranty: 5 years




- RPS mode: provide N+1 redundancy to M4300-52G-PoE+ when its two internal PSUs are used in EPS (shared) mode
- One APS1000W per M4300-52G-PoE+ connected to the RPS4000 unit
  - Up to four (4) M4300-52G-PoE+ switches per RPS4000 unit



- Front view**
- RPS4000 is 1RU unit with four (4) empty slots
- Rear view**
- Four (4) embedded RPS connectors
  - Switch selectors for RPS/EPS power modes
- Included:**
- Four (4) RPS cables – 60cm each (~2 ft)
  - Rack mount kit

Direct Attach Cables for M4300 series

ORDERING INFORMATION WORLDWIDE: SEE TABLE BELOW WARRANTY: 5 YEARS	SFP+ to SFP+	
	1 meter (3.3 ft)	3 meters (9.8 ft)
<p>10 Gigabit DAC</p>  <p>• Fits into M4300 models SFP+ interfaces</p>	<p><b>AXC761</b></p> <p>10GSFP+ Cu (passive) SFP+ connectors on both end</p> <p><b>AXC761-10000S (1 unit)</b></p>	<p><b>AXC763</b></p> <p>10GSFP+ Cu (passive) SFP+ connectors on both end</p> <p><b>AXC763-10000S (1 unit)</b></p>

## Components

### APS1000W Power Supply Unit

#### Ordering information

- Americas, Europe: APS1000W-100NES
- Asia Pacific: APS1000W-100AJS
- Warranty: 5 years



- Power module for RPS4000 unit
- Additional PSU for M4300-28G-PoE+ (GSM4328PB) and M4300-52G-PoE+ (GSM4352PB)
- C15 connector
- Capacity:
  - 110V-240V AC power input
  - Up to 640W output power at 110V AC
  - Up to 910W output power at 220V AC

### APS550W Power Supply Unit

#### Ordering information

- Americas, Europe: APS550W-100NES
- Asia Pacific: APS550W-100AJS
- Warranty: 5 years



- Additional PSU for M4300-28G-PoE+ (GSM4328PA) and 4300-52G-PoE+ (GSM4352PA)
- C14 connector
- Capacity:
  - 110V-240V AC power input
  - Up to 575W output power at 110/220V AC

### APS250W Power Supply Unit

#### Ordering information

- Americas, Europe: APS250W-100NES
- Asia Pacific: APS250W-100AJS
- Warranty: 5 years



- Additional PSU for M4300-8X8F, M4300-12X12F and M4300-24X24F
- C14 connector
- Capacity:
  - 110V-240V AC power input
  - Up to 250W output power at 110/220V AC

### APS150W Power Supply Unit

#### Ordering information




- Americas, Europe: APS150W-100NES
- Asia Pacific: APS150W-100AJS
- Warranty: 5 years



- Additional PSU for M4300-28G and M4300-52G
- C14 connector
- Capacity:
  - 110V-240V AC power input
  - Up to 150W output power at 110/220V AC

## Accessories

### GBIC SFP and SFP+ Optics for M4300 series

Ordering information • Worldwide: see table below • Warranty: 5 years	Multimode Fiber (MMF)		Single mode Fiber (SMF)
	OM1 or OM2 62.5/125µm	OM3 or OM4 50/125µm	9/125µm
<b>10 Gigabit SFP+</b>    • Fits into M4300 models SFP+ interfaces	<b>AXM763</b>  10GBase-LRM long reach multimode 802.3aq - LC duplex connector  up to 220m (722 ft)  <b>AXM763-10000S (1 unit)</b>	<b>AXM763</b>  10GBase-LRM long reach multimode 802.3aq - LC duplex connector  up to 260m (853 ft)  <b>AXM763-10000S (1 unit)</b>  <b>AXM761</b>  10GBase-SR short reach multimode LC duplex connector  OM3: up to 300m (984 ft) OM4: up to 550m (1,804 ft)  <b>AXM761-10000S (1 unit)</b> <b>AXM761P10-10000S (pack of 10 units)</b>	<b>AXM762</b>  10GBase-LR long reach single mode LC duplex connector  up to 10km (6.2 miles)  <b>AXM762-10000S (1 unit)</b> <b>AXM762P10-10000S (pack of 10 units)</b>  <b>AXM764</b>  10GBase-LR LITE single mode LC duplex connector  up to 2km (1.2 mile)  <b>AXM764-10000S (1 unit)</b>
<b>Gigabit SFP</b>    • Fits into M4300 models SFP+ interfaces	<b>AGM731F</b>  1000Base-SX short range multimode LC duplex connector  up to 275m (902 ft)  <b>AGM731F (1 unit)</b>	<b>AGM731F</b>  1000Base-SX short range multimode LC duplex connector  OM3: up to 550m (1,804 ft) OM4: up to 1,000m (3,280 ft)  <b>AGM731F (1 unit)</b>	<b>AGM732F</b>  1000Base-LX long range single mode LC duplex connector  up to 10km (6.2 miles)  <b>AGM732F (1 unit)</b>
<b>AGM734</b> <b>1000Base-T Gigabit RJ45 SFP</b>	Ordering information • Worldwide: AGM734-10000S • Warranty: 5 years		• Fits into M4300 models SFP+ interfaces • 1 port Gigabit RJ45 • Supports only 1000Mbps full-duplex mode • Up to 100m (328 ft) with Cat5 RJ45 or better • Conveniently adds copper connectivity to M4300 fiber interfaces

\* This product comes with a limited warranty that is valid only if purchased from a NETGEAR authorized reseller and modifications to product may void the warranty; covers hardware, fans and internal power supplies – not software or external power supplies See <http://www.netgear.com/about/warranty/> for details. Lifetime technical support includes basic phone support for 90 days from purchase date and lifetime online chat support when purchased from a NETGEAR authorized reseller.

NETGEAR, the NETGEAR Logo, and ProSAFE are trademarks of NETGEAR, Inc. in the United States and/or other countries. Other brand names mentioned herein are for identification purposes only and may be trademarks of their respective holder(s). Information is subject to change without notice. © 2016 NETGEAR, Inc. All rights reserved.