SECURE, COMPACT AND CLOUD-CONNECTED DEVICES WITH A TOP SPEED OF 40PPM



i-SENSYS MF460 Series

The i-SENSYS MF460 Series consists of multifunction black & white laser printers designed for small businesses.









Protect documents

Protect your documents, device and network with 360-degree security. Features include TLS1.3, Verify System at Startup, Secure PIN print

Intuitive user experience

Easily carry out print and scanning jobs with one-touch Application Library buttons. Drag & Drop icons allow you to customise the display screen and perform routine tasks seamlessly.

Boost productivity

Save valuable time with print speeds of up to 40ppm, scanning speeds of 100ipm and a warm-up time of 14 seconds. Meet demand by using Universal Print to access your device from anywhere.

Collaborate in the cloud

Harness the power of the cloud with built-in connectivity to cloud storage services including Google Drive, DropBox, and OneDrive.



RANGE FEATURE STEP UP CHART

Single Pass Duplex Scan

Wireless connectivity



MF461dw



MF463dw



MF465dw

Fax			•
A4 print speed	36ppm	40ppm	40ppm
Display	12.7cm colour touch screen	12.7cm colour touch screen	12.7cm colour touch screen
Secure PIN print	•	•	•
Duplex printing	•	•	•
Built-in cloud connectivity	•	•	•
Application Library	•	•	•



TECHNICAL SPECIFICATIONS

i-SENSYS MF460 Series

Mono Laser All-In-One Machine type

Available functionsw MF465dw: Print, Copy, Scan and Fax MF463dw/MF461dw: Print, Copy, Scan

MF465dw/MF463dw:
Single sided: Up to 40 ppm (A4)
Up to 65.4 ppm(A5-Landscape)
Double sided: Up to 53.6 ipm (A4)
MF461dw:
Single sided: Up to 33.6 ipm (A4)
Up to 58.8 ppm(A5-Landscape)
Double sided: Up to 30.2 ipm (A9)

Printing method Monochrome laser beam printing

Print resolution Up to 1200 x 1200 dpi

Warm-up time Approx. 14 seconds or less from power on

First Print Out Time Approx: 5.0 seconds or less UFRII. PCL 5e2. PCL6. Adobe® PostScript3 Printer languages

45 PCL fonts 136 PostScript fonts

Print margins 5 mm-top, bottom, left and right 10 mm-top, bottom, left and right (Envelope)

Toner saver mode

Advanced printing features

rea

Encrypted Secure Print

Secure Print

Print from USB memory key (JPEG/TIFF/PDF)

Print from Cloud (Dropbox, GoogleDrive, OneDrive)

(PDF/JPEG)

Microsoft Universal Print

IOS: AliPrint, Canon PRINT Business app

Android: Mopria certified, Canon PRINT Business app, Canon Print

Service Plug-in

MF465dw/MF463dw: Single sided (A4): Up to 40 ppm Double sided (A4): Up to 33.6 ipm MF461dw: Single sided (A4): Up to 36 ppm Double sided (A4): Up to 30.2 ipm

First Copy Output Time (FCOT) Approx. 6.1 seconds or less

Up to 600 x 600 dpi Copy resolution

Copy modes Text/Photo, Text/Photo (High speed), Photo, Text

Double sided copying 1-sided to 2-sided (Automatic)

Multiple copy Up to 999 copies

Reduction / Enlargement 25-400% in 1% increments

Other features Collate Copies, 2 on 1, 4 on 1, ID card copy, Passport copy

SCANNER

Scan resolution Optical: Up to 600 x 600 dpi Enhanced: Up to 9600 x 9600 dpi

Single sided mono: S0ipm (300x300dpi) Single sided colour: 40ipm (300x300dpi) Double sided mono: 100ipm (300x300dpi) Double sided mono: 100ipm (300x300dpi) Double sided colour: 80ipm (300x600dpi) Single sided mono: 40ipm (300x600dpi) Single sided mono: 40ipm (300x600dpi) Double sided mono: 80ipm (300x600dpi) Double sided mono: 80ipm (300x600dpi) Scan speed

Colour scanning depth 24 bit/24 bit (input/output) Greyscales 256 levels

Compatibility May scan width 216mm

TIFF/JPEG/PDF/Compact PDF/Searchable PDF

Scan to E-mail Scan to PC Interface and connectivity Scan to USB memory key Scan to FTP

Scan to Cloud¹

MF465dw ONLY

33.6 Kbps (Up to 3 seconds/page⁴) Modem speed

Receive mode Fax only, Fax/Tel Auto Switch, Answer Mode, Manual

TIFF/JPEG/PDF/PNG3

Fax resolution

FAX memory Up to 256 pages³ Speed dials Up to 104 dials Group dials/destinations

Sequential broadcast Max. 114 destinations Permanent fax memory backup (Backup with flash memory)

Memory backup

Double sided faxing Yes (Transmit and Receive)

Other features Sender's Name (TTI), Direct Send, TX Report, Sequential Broadcasting

MEDIA HANDLING

Scanner type Platen, 2-sided ADF (single pass)

Paper input (Standard) 250-sheet cassette 100-sheet multi-purpose tray 50-sheet ADF

Paper input (Option) 550-sheet cassette Maximum paper input capacity 900 sheets Paper output

Media types Plain paper, Recycled paper, Heavy Paper, Thin paper, Label, Post card, Media sizes

Cassette (Standard and optional): A4, A5, A5 (Landscape), A6, B5, Legal, Letter, Executive, Statement, OFFICIO, B-OFFICIO, M-OFFICIO, GLTR, GLGL, Foolscap, 16K, Custom sizes: Min. 105 x 148 mm Max. 216.0 x 355.6 mm.

sizes: Min. 105 x 148 mm Max. 216.0 x 355.6 mm. Multi-purpose tray: A4, A5, A5 (Landscape), A6, B5, Legal, Letter, Executive, Statement, OFFICIO, B-OFFICIO, M-OFFICIO, GLTR, GLGL, Foolscap, 16K, Indexcard, Envelope (COMIO, Monarch, C5, DL), Custom sizes: Min 76.2 x 127 mm Max. 216.0 x 355.6 mm. A2, A5, A6, B5, Legal, Letter, Statement, Custom sizes: Min. 105 x 128 mm Max 215.9 x 355.6 mm.

Cassette (standard and optional): 60 to 120 g/m² Multi-purpose tray: 60 to 199 g/m² ADF: 60 to 120 g/m²

A4, Legal, Letter, OFFICIO, B-OFFICIO, M-OFFICIO, GLGL, Foolscap Custom size - Min. 210 x 279.4 mm Max. 216.0 x 355.6 mm 60 to 120 g/m² Double sided printing

INTERFACE & SOFTWARE

Media weights

Interface type USB 2.0 Hi-Speed, 10BASE-T/100BASE-TX/1000Base-T, Wireless 802.11b/g/n, Wireless Direct Connection

Windows* 11 / Windows* 10 / Server* 2022 / Server* 2019 / Server* 2016 // Server* 2012 / Server* 2012 / Server* 2019 / Server* 2016 // Mac OS X version 10.13 & up Linux* Operating System compatibility

Network Protocol

Print:
TCP/IP (LPD/Port9100/IPP/IPPS/WSD)
Scan:
Push Scan: File: FTP (TCP/IP), SMB3.0 (TCP/IP)
E-mail/I-Fax: SMTP (send), POP3 (receive)
Pull Scan: TCP/IP
Management:
SMMPNJ, SMMPV3 (IPV4,IPV6)
Socuritor:

Security: TLS1.3, IPSec, IP address filtering, IEEE802.1X, SNMPv3, SSL (HTTPS, IPPS)

IPPS)
Security (wireless):
Infrastructure Mode:
WPP(64/128 bit), WPA-PSK(TKIP/AES), WPA2-PSK
(TKIP/AES), WPA-EAP(AES), WPA2-EAP(AES)
Access Point Mode:
WPA2-PSK(AES)

Software and printer management

WPA2-PSK(AES)
MF Scan Utility,
Remote User Interface (RUI),
Remote User Interface (RUI),
Remote Departion Viewer
Department ID Management,
Toner Status Tool,
IW Enterprise Management Console: Server-based software for
centralised management of a fleet of devices
eMaintenance: embedded RDS allows remote eMaintenance services
such as meter capture, automatic consumables management and remote
diagnostics
Application Library

GENERAL FEATURES

Recommended Monthly Print Volume 750 - 4,000 pages per month

Max. 80,000 pages per month⁶ Duty cycle 1200MHz Processor Speed

Memory 1GB Storage

Control panel 12.7 cm I CD Colour Touch Screen Dimensions with trays (W x D x H) 420 mm x 460 mm x 375 mm 689 mm v 1 081 mm v 824 mm

Installation space (W x D x H)

Operating environment Temperature: 10 to 30°C (50 to 86°F) Humidity: 20 to 80% RH (no condensa

220-240V(±10%) 50/60Hz (±2Hz) Assimum: Approx. 1,280 W
Active printing: Approx. 480W
Standby: Approx. 8W
Sleep mode: Approx. 9.9 W
Typical Electricity Consumption (TEC):
MF465dw/MF465dw: 0,32 kWh/week (230V)¹
MF461dw: 0,31 kWh/week (230V)²
For detailed information relating to Lot26 regulation, please go to:
http://www.canon-europe.com/For_Work/Lot26/index.aspx Power Consumption

Sound Pressure⁷: MF465dw/MF463dw:

MF465dw/MF463dw: Active: 53 dB Standby: Inaudible® MF461dw: Active: Simplex 53dB / Duplex 52dB Standby: Inaudible® Scund Power: Active: Duplex 68dB / Simplex 67dB Standby: Inaudible®

CONSUMABLES

Cartridges Cartridge 070 (3,000 pages⁹)¹⁰ Cartridge 070H (10,200 pages⁹)¹⁰

CST.Feeding Module-AH1 (550-sheet cassette) MF465dw ONLY TEL 6 Kit Long Cord (Telephone handset) Items

- [1] Subscription to a third party cloud service is required, and subject to their party terms and conditions.
- ^[2] A Canon PCI 5e driver is not supplied however PCI 5e commands are supported on the device
- [3] Scan by MF Scan Utility or Canon PRINT Business
- [4] Based on ITU-T Standard Chart No. 1
- [5] Linux support both printing and scanning
- ⁽⁶⁾ Duty cycle is defined as the maximum number of printed pages for a single peak month. Any usage above the recommended duty cycle may decrease the life of the product
- Declared noise emission in accordance with ISO 9296
- Inaudible means that the emission sound pressure level for a bystander is lower than absolute standard for background noise in accordance with ISO 7779
- [9] Based on ISO/IEC 19752
- [10] Printer ships with Cartridge 070 (3,000 pages)
- As per US ENERGY STAR* version3.0.



SECURE, COMPACT AND CLOUD-CONNECTED DEVICES WITH A TOP SPEED OF 40PPM

The i-SENSYS MF460 Series consists of multifunction black & white laser printers designed for small businesses.



PRODUCT DETAILS:

PRODUCT NAME	Mercury Code	EAN Code
i-SENSYS MF465dw	5951C007AA	4549292214901
i-SENSYS MF463dw	5951C008AA	4549292214918
i-SENSYS MF461dw	5951C020AA	4549292221299

ACCESSORIES

PRODUCT NAME	Mercury Code	EAN Code
Cassette Feeding Module-AH1	0732A033BA	4549292092769
Telephone 6 Kit EU (CW)	0752A054AA	4960999453910

CONSUMABLES:

PRODUCT NAME	Mercury Code	EAN Code
Cartridge 070	5639C002AA	4549292197839
Cartridge 070 H	5640C002AA	4549292198041

Canon Inc. canon.com

Canon Europe canon-europe.com

English edition © Canon Europa N.V.,2023

