

# i-tec USB 3.0 / USB-C / Thunderbolt 3 Professional Dual 4K Display Docking Station Generation 2 + Power Delivery 100W

i-tec USB 3.0 / USB-C / Thunderbolt 3 Professional Dual 4K Display Docking Station Generation 2 + Power Delivery 100W



## **PRODUCT DESCRIPTION**

A powerful office docking station supporting super-fast USB Gen 2 ports with fast charging. Dock supports output to up to two external monitors in up to 4K high resolution. The dock can be used with virtually all notebooks as it supports connection to all common ports: USB 3.0, USB-C and Thunderbolt" 3/4, while supporting all common current operating systems. Plenty of USB ports (two USB-C support Gen 2 speeds of up to 10 Gbps), reliable and fast connection to the corporate network thanks to the integrated LAN port and support for installation behind the monitor all make this docking station the ideal companion for true professionals. Of course, it supports charging of your laptop or tablet, up to 100 W.

- Connect to 2 external monitors in resolutions up to 4K
- Power delivery: up to 100 W
- 2 DisplayPort and 2 HDMI ports available
- 2x USB-C Gen 2 (10 Gbps), 2x USB-A 3.2 Gen 2 (10 Gbps) and 3x USB-A 3.2 Gen 1 (5 Gbps) allow you to easily connect your USB devices and peripherals.
- USB ports support fast charging: USB-C provides PD up-to 20 W, two additional ports support BC 1.2 fast charging.
- Gigabit Ethernet RJ-45 provides reliable, robust and high-speed internet connectivity with support for 10/100/1000 Mbps speeds.
- Combo jack for audio and microphone, very high quality 32bit/192 kHz sampling rate
- Kensington lock provides anti-theft protection, especially in shared office environments or public areas
- Docking station power switch allows for maximum power savings
- Docking station supports a VESA mount for smart vertical installation behind a VESA-enabled monitor
- Supports Windows 10 / 11, macOS, Android 5 or later, Chrome OS R51 or later, Linux Ubuntu

NOTE: If the docking station is connected via USB 3.0 port, charging is not supported.

## **PRODUCT FEATURES**

- 1x USB-C port for connecting to the host device with USB-C or USB-A port (cable USB-C and adapter from USB-C to USB 3.0 is included)
- Docking station technology: <u>DisplayLink</u> + <u>USB-C PD</u>



- Power Delivery: 96W
- Video Ports:
  - 2x Display Port (DP++ support)
  - ∘ 2x HDMI
- Supported Resolutions:
  - ∘ 1 monitor 1x DP → up to 4K/60Hz
  - 1 monitor 1x HDMI  $\rightarrow$  up to 4K/60Hz
  - 1 monitor 2x DP  $\rightarrow$  up to 5K/60Hz\*
  - ∘ 2 monitors 1x DP + 1x DP → up to 2x 4K/60Hz
  - ∘ 2 monitors 1x DP + 1x HDMI → up to 2x 4K/60Hz
  - ∘ 2 monitors 1x HDMI + 1x HDMI → up to 2x 4K/60Hz
- 1x USB-C 3.2 port Gen 2 (data only), BC 1.2
- 1x USB-C 3.2 port Gen 2, PD 20W
- 1x USB 3.2 port Gen 2, BC 1.2
- 1x USB 3.2 port Gen 2
- 3x USB 3.2 port Gen 1
- 1x Ethernet GLAN RJ-45 port (DisplayLink DL-6950)
- 1x 3.5 mm Combo Audio port, supporting high quality 32bit/192 kHz sampling rate and record
- 1x Power input (DC 20V/7,5A)
- MAC Address cloning: Yes (using *i-tec Docker Pro* software)
- WOL: S1, S2, S3
- On/Off switch to turn the docking station on and off
- LED indicator
- Kensington lock support
- VESA mounting support
- USB-C cable with USB-C to USB-A adapter (100 cm)
- OS: Windows 10 / 11, macOS, Android 5 or later, Chrome OS R51 or later, Linux Ubuntu
- Easy driver installation (Windows, MacOS, Ubuntu, Android (external link))
- Product dimensions: 190x88x37 mm
- Product weight: 539 g
- Package dimensions: 253 x 200 x 54 mm

\* 5K resolution is only supported by Windows

#### Hardware requirements:

• Devices with a free USB-A, USB-C, USB4 or Thunderbolt<sup>™</sup> 3/4 port

#### **Requirements for the Power Delivery function:**

• Devices with a free USB-C, USB4 or Thunderbolt<sup>™</sup> 3 port with "Power Delivery" support

#### **Operating system:**

• Windows 10 / 11, macOS, Android 5 or later, Chrome OS R51 or later, Linux Ubuntu

If the docking station is connected via USB 3.0, charging of laptops and tablets is not supported.

### **SPECIFICATION**

Part Number	Product Description & EAN
CADUAL4KDOCKPD2	i-tec USB 3.0 / USB-C / Thunderbolt 3 Professional Dual 4K Display Docking Station Generation 2 + Power Delivery 100W EAN: 8595611706394
CADUAL4KDOCKPD2UK	i-tec USB 3.0 / USB-C / Thunderbolt 3 Professional Dual 4K Display Docking Station Generation 2 + Power Delivery 100W EAN: 8595611706677



Hardware		
Bus type	USB-C, USB-3.0	
System Requirements		
Operating system	Windows XP / Vista / 7 / 8 / 8.1 / 10 Windows 7 / 8 / 8.1 /10 Windows 8 / 8.1 /10 Windows 10 macOS X Linux Linux Ubuntu 14.04, 16.04, 17.04, 17.10, 18.04, 19.04 Chrome OS R51 or laterWindows 10 - Automatic installation of OS drivers. Other operating systems - manual driver installation. Firmware updates automatically.	
Other features		
Colour	black	
Housing Material	ABS	
Product Dimensions	190 x 88 x 37 mm	
Product Weight	539 g	
Package Weight	789 g	
Packaging Dimensions (LxWxH)	253 x 200 x 54 mm	
Support		
Warranty period	2 years	
Technical support	lifetime	
Package contents		
Product		
Power adapter 150W		
USB-C to USB-C/USB-A cable (100cm)		
Manual		

For further information regarding setup or for answers to FAQ's, please visit our website <u>i-tec.pro</u>. Specifications are subject to change without notice.

Updated 24.8.2023