COMPACT KEYBOARD WITH INTEGRATED TRACKBALL
AK-4400-T SERIES INDUSTRIAL KEY

FEATURES & BENEFITS

+ High Reliable, Compact Keyboard
+ Full Size Desktop Key Caps
+ Flat Key Profile for Easy Cleaning
+ Scissors Balancing Technology
+ Low Profile for Implementations in space critical applications

+ Up to 10 Mio. Cycles per Key
+ **Option I:** Exchangeable PU-Cover for Key Field
+ **Option II:** Fully taped PU-Cover
+ Optical Trackball for Mouse Replacement, 1000 dpi
+ German Brand Product

TECHNICAL DATA			
Compatibility		x	All operating systems supporting USB resp. PS/2 Keyboards
Temperature Range		x	Storage –20° to +60°C; Operation 0° to +50°C
Interface		x	USB 1.1 or PS/2
Supply Voltage		x	5 V +5%/-10% through USB Port resp. 5V +/-5% through PS/2 Port
Current Consumption		x	Appr. 100mA (Low Power Device)
Dimensions		x	Appr. 370 x 139 x 23.5mm
Weight		x	Appr. 700g
LED Status Indicators		x	Caps Lock, Num Lock, Scroll Lock, Power On
Key Travel / Key Actuation Force		x	Appr. 2,5 +/- 0,5 mm / Appr. 60g - similiar to Notebook Keyboard
Key Strokes Life		x	5 million cycles at halve size keys, 10 million cycles at full size keys
Agency Approvals		x	CE, FCC

PART NO. / ORDER NO.

Example: Keyboard AK-4400-T cabled, USB, light grey, German	AK-4400-TU	-	W	-	GE
Cabled, USB Interface	AK-4400-TU	-	y	-	x
Cabled, PS/2 Interface	AK-4400-TP	-	y	-	x
Cabled, USB Interface, PU Protection Cover, fully taped	AK-F4400-TUV	-	y	-	x
Cabled, PS/2 Interface, PU Protection Cover, fully taped	AK-F4400-TPV	-	y	-	x
PU Protection Cover	AK-F4400				

Identifier z Version/Option	Identifier y Color	Identifier x Country Layout
Version: cabled* U = USB-Connector (Standard) P = PS/2-Connector UV = USB Connector, fully taped PU-Cover PV = PS/2 Connector, fully taped PU-Cover	W = Light Grey B = Black	GE = German FR = French UK = UK English All other Euopean layouts are available at Active Key.

Datasheet AK-4400-T
12-05-30