




SPECIAL FEATURES




- ❖ High Efficiency, 80 PLUS® Gold Certified
- ❖ Fully Modular Cabling Design
- ❖ Compact Size
- ❖ SFX to ATX Expandability
- ❖ 92 mm Fluid Dynamic Bearing (FDB) Fan
- ❖ Seasonic Hybrid Silent Fan Control
- ❖ Highly Reliable Japanese 105 °C Aluminum Electrolytic Capacitors
- ❖ Tight Voltage Regulation (12 V, 5 V and 3.3 V) [± 3%]
- ❖ Cable-free Connection Design
- ❖ 10 Years Warranty

POWER DISTRIBUTION

Model	+3.3 V	+5 V	+12 V	-12 V	+5 Vsb	Total Power
FOCUS SGX-750	20 A	20 A	62 A	0.3 A	3 A	750 W
	130 W		744 W	3.6 W	15 W	
FOCUS SGX-650	20 A	20 A	54 A	0.3 A	3 A	650 W
	120 W		648 W	3.6 W	15 W	
FOCUS SGX-550	20 A	20 A	45 A	0.3 A	3 A	550 W
	100 W		540 W	3.6 W	15 W	



CONNECTOR QUANTITY

Cable					
Model	Main Power (24P / 20P) 350 mm	EPS 12 V / ATX 12 V (8P / 4P) 400 mm	PCI-E (8P / 6P)	SATA	Peripheral (4P)
FOCUS SGX-750	1	2	4	6	3
FOCUS SGX-650	1	2	4	6	3
FOCUS SGX-550	1	1	2	3	3

10 YEARS WARRANTY



Safety & EMI / EMC



Protection Features: OPP / OVP / UVP / SCP / OCP / OTP

Dimensions: 125 mm (L) x 100 mm (W) x 63.5 mm (H)



Specifications may change without prior notice



Headquarters sales@seasonic.com
USA ssa.sales@seasonic.com
Europe sse.sales@seasonic.com

www.seasonic.com