Usher in a new era of domination.







Seagate FireCuda 530R SSD

Usher in a new era of domination.

FireCuda 530R SSD, the latest evolution of our bestselling PCIe Gen4 SSD, unleashes ultra-fast speeds, extreme durability and unrivalled performance. With leading-edge components in a slim M.2 2280 form factor, it's ideal for pro-level gamers and creators. FireCuda 530R SSD supports Microsoft[™] DirectStorage for seamless gaming, and is available in 1 TB, 2 TB or 4 TB capacities.



Key Features

Peak Performance

Level up with ultra-fast PCIe Gen4 SSD speeds for accelerated gaming and content creation

Easy Gaming

Supports Microsoft's DirectStorage technology for faster load times.

Tough Stuff

Extremely durable, with endurance of up to 5,050 TBW

Usher in a new era of domination.



SEAGATE FIRECUDA 530R SSD

Inside & Out

Built with leading edge components including the Seagate validated E18 controller, all in a slim M.2 2280 form factor

High Capacity

Choose from 1 TB, 2 TB, or 4 TB capacity options for all your gaming needs

No worries

Backed by 5-year warranty, 3-years Rescue Services¹, and SeaTools 5 support 1 Rescue Data Recovery <u>Services not available in all countries</u>.



| RETAIL PACKAGING | BOX DIMENSIONS | MASTER CARTON DIMENSIONS | PALLET DIMENSIONS |
|---------------------------|----------------|--------------------------|-------------------|
| Length (in/mm) | 6.102in/155mm | 11.496in/292mm | 47.992in/1219mm |
| Width (in/mm) | 4.291in/109mm | 6.024in/153mm | 20in/508mm |
| Depth (in/mm) | 0.945in/24mm | 5.512in/140mm | 27.795in/706mm |
| Weight (lb/kg) | 0.154lb/0.07kg | 2.138lb/0.97kg | 105.822lb/48kg |
| QUANTITIES | | | |
| Boxes per Master Carton | 10 | | |
| Master Cartons per Pallet | 48 | | |
| Pallet Layers | 4 | | |

SYSTEM REQUIREMENTS

WHAT'S INCLUDED

- M.2 (M key) slot, PCIe[®] G4 ×4 interface (backwards compatible with PCIe G3 interface)
- Seagate[®] FireCuda[®] 530 SSD

- interface) Windows [®] 11, Windows 10
- Linux

| REGION | MODEL NUMBER | CAPACITY | LIMITED WARRANTY (YEARS) | UPC CODE | EAN CODE | MULTI-PACK UPC |
|--------|---------------|----------|-----------------------------|--------------|---------------|----------------|
| ww | ZP1000GM3A063 | 1000GB | 5 | 763649183083 | 8719706437691 | 10763649183080 |
| ww | ZP2000GM3A063 | 2000GB | 5 | 763649183090 | 8719706437707 | 10763649183097 |
| ww | ZP4000GM3A063 | 4000GB | 5 | 763649183106 | 8719706437714 | 10763649183103 |

Usher in a new era of domination.

SEAGATE FIRECUDA 530R SSD

| SPECIFICATIONS | FIRECUDA 530R SSD | | | | | |
|--|-----------------------|-----------------------|-----------------------|--|--|--|
| Capacity | 4TB | 2ТВ | 1TB | | | |
| Standard Model | ZP4000GM30063 | ZP2000GM30063 | ZP1000GM30063 | | | |
| nterface | PCIe Gen4 ×4 NVMe 1.4 | PCIe Gen4 ×4 NVMe 1.4 | PCle Gen4 ×4 NVMe 1.4 | | | |
| NAND Flash Memory | 3D TLC | 3D TLC | 3D TLC | | | |
| Form Factor | M.2 2280-D2 | M.2 2280-D2 | M.2 2280-D2 | | | |
| PERFORMANCE | | | | | | |
| Sequential Read (Max, MB/s), 128 KB ¹ | 7,400 | 7,400 | 7,400 | | | |
| Sequential Write (Max, MB/s), 128 KB ¹ | 6,800 | 6,900 | 7,000 | | | |
| Random Read (Max, IOPS), 4 KB QD32 T16 ¹ | 1,300,000 | 1,300,000 | 1,300,000 | | | |
| Random Write (Max, IOPS), 4 KB QD32 T16 ¹ | 1,300,000 | 1,300,000 | 1,300,000 | | | |
| ENDURANCE/RELIABILITY | | | | | | |
| Total Bytes Written (TB) | 5,050 | 2,400 | 1,100 | | | |
| Mean Time Between Failures (MTBF, hours) | 1,800,000 | 1,800,000 | 1,800,000 | | | |
| Rescue Data Recovery Services (years) ² | 3 | 3 | 3 | | | |
| Narranty, Limited (years) | 5 | 5 | 5 | | | |
| POWER MANAGEMENT | | | | | | |
| Active Power, Average (W) | 8.9 | 8.6 | 8.3 | | | |
| dle Power PS3, Average (mW) | 29 | 28 | 22 | | | |
| ow Power L1.2 mode (mW) | <5 | <5 | <5 | | | |
| INVIRONMENTAL | | | | | | |
| emperature, Operating Internal (°C) | 0 to 70 | 0 to 70 | 0 to 70 | | | |
| emperature, Non-operating (°C) | -40 to 85 | -40 to 85 | -40 to 85 | | | |
| Shock, Non-operating: 0.5 ms (Gs) | 1,500 | 1,500 | 1,500 | | | |
| SPECIAL FEATURES | | | | | | |
| RIM | Yes | Yes | Yes | | | |
| S.M.A.R.T. | Yes | Yes | Yes | | | |
| RoHS compliance | Yes | Yes | Yes | | | |
| PHYSICAL | | | | | | |
| ength (mm/in, max) | 80.85 mm/3.183 in | 80.85 mm/3.183 in | 80.85 mm/3.183 in | | | |
| Nidth (mm/in, max) | 22.15 mm/0.872 in | 22.15 mm/0.872 in | 22.15 mm/0.872 in | | | |
| Height (mm/in, max) | 3.58 mm/0.140 in | 3.58 mm/0.140 in | 2.23 mm/0.087 in | | | |
| Weight (Ib/g) | 9.2g/0.020lb | 8.8g/0.019lb | 7.3g/0.016lb | | | |

1 Fresh out of box (FOB) performance obtained on newly formatted drive. Performance may vary based on SSD's firmware version, system hardware, and configuration. Performance based on CrystalDiskMark v.7.0.0 x64 on Windows 10 host with PCIe Gen4 motherboard.

2 Rescue Data Recovery Services not available in all countries.

SEAGATE.COM

© 2024 Seagate Technology LLC. All rights reserved. Seagate, Seagate Technology, and the Spiral logo are registered trademarks of Seagate Technology LLC in the United States and/or other countries. FireCuda is either a trademark or registered trademark of Seagate Technology LLC or one of its affiliated companies in the United States and/or other countries. The NVMe word mark and/or NVMExpress design mark are trademarks of NVMExpress, Inc. The PCIe word mark and/or PCIExpress design mark are registered trademarks and/or service marks of PCI-SIG. All other trademarks or registered trademarks are the property of their respective owners. When referring to drive capacity, one gigabyte, or GB, equals one billion bytes and one terabyte, or TB, equals one trillion bytes. Your computer's operating system may use a different standard of measurement and report a lower capacity. In addition, some of the listed capacity is used for formatting and other functions, and thus will not be available for data storage. Actual data rates may vary depending on operating environment and other factors, such as chosen interface and disk capacity. Seagate reserves the right to change, without notice, product offerings or specifications. DS7.1-2403US