

CyberPower PR1500ERTXL2UC uninterruptible power supply (UPS) Line-Interactive 1.5 kVA 1500 W 10 AC outlet(s)

Brand : CyberPower

Product code: PR1500ERTXL2UC

Product name : PR1500ERTXL2UC



CyberPower PR1500ERTXL2UC. UPS topology: Line-Interactive, Output power capacity: 1.5 kVA, Output power: 1500 W. AC outlet types: C13 coupler, Power plug: C14 coupler, AC outlets quantity: 10 AC outlet(s). Battery technology: Sealed Lead Acid (VRLA), Typical backup time at full load: 6.5 min, Typical backup time at half load: 19.3 min. Form factor: Rackmount/Tower, Product colour: Black, Housing material: Metal. Width: 433 mm, Depth: 500 mm, Height: 86.5 mm



Features		Battery	
UPS topology *	Line-Interactive	Number of batteries supported	1
Output power capacity *	1.5 kVA	Typical backup time at full load	6.5 min
Output power *	1500 W	Typical backup time at half load	19.3 min
Waveform *	Pure sine	Battery recharge time	3 h
Input operation voltage (min) *	148 V	Hot-swap battery	✓
Input operation voltage (max) *	288 V	Design	
Input frequency *	50/60 Hz	Form factor *	Rackmount/Tower
Output operation voltage (min)	220 V	Housing material	Metal
Output operation voltage (max)	240 V	Rack capacity	2U
Output frequency	50/60 Hz	Extended battery module rack capacity	2U
Automatic Voltage Regulation (AVR)	✓	Cable length	3.05 m
Maximum current	16 A	Cooling type	Active
Surge energy rating	2430 J	Built-in fan	✓
Response time	6 ms	Product colour *	Black
Heat dissipation	96.7 BTU/h	Control type	Buttons
Number of input phases	1	Display type	LCD
Number of output phases	1	LED indicators	✓
Output power factor	1	Operational conditions	
Power Factor Correction (PFC) type	Active	Operating temperature (T-T)	0 - 40 °C
Emergency Power Off (EPO)	✓	Storage temperature (T-T)	-15 - 45 °C
EMI/RFI noise filtering	✓	Operating relative humidity (H-H)	0 - 95%
Surge protection	✓	Storage relative humidity (H-H)	0 - 95%
Power protection features	Overload	Operating altitude	0 - 3000 m
Audible alarm modes	Alarm when on battery, Fault, Low battery alarm, Overload alarm	Non-operating altitude	0 - 15000 m
Power source type	AC	Technical details	
Detachable power cord	✓	Sustainability compliance	✓
Country of origin	China	Compliance certificates	CE, Federal Communications Commission (FCC), RCM, RoHS, UL, VCCI
Ports & interfaces		Packaging content	
AC outlet types	C13 coupler	Batteries included	✓
Power plug	C14 coupler		
AC outlets quantity	10 AC outlet(s)		
USB port	✓		

Ports & interfaces		Weight & dimensions	
USB 2.0 ports quantity	1	Width	433 mm
USB port type	USB Type-B	Depth	500 mm
Serial interface	✓	Height	86.5 mm
Serial interface type	RS-232	Weight	32 kg
Serial ports quantity	2	Package width	560 mm
RS-232 ports	2	Package depth	620 mm
Ethernet LAN (RJ-45) ports	2	Package height	275 mm
Emergency Power Off (EPO) connector	✓	Package weight	38.8 kg
		Package type	Box
Battery		Packaging data	
Battery technology	Sealed Lead Acid (VRLA)	Rack mount kit	✓
		Cables included	Serial
		Manual	✓
		Other features	
		Battery type	RBP0128



4711027798912

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 20-OCT-2024. Prints or copies of Information are only valid on the printed Publication date