

CyberPower PR3000ERT2UC uninterruptible power supply (UPS) Line-Interactive 3 kVA 3000 W 10 AC outlet(s)

Brand : CyberPower

Product code: PR3000ERT2UC

Product name : PR3000ERT2UC



2U, IEC C13 x 10, LCD, Sine

CyberPower PR3000ERT2UC. UPS topology: Line-Interactive, Output power capacity: 3 kVA, Output power: 3000 W. AC outlet types: C13 coupler, Power plug: C14 coupler, AC outlets quantity: 10 AC outlet(s). Battery technology: Sealed Lead Acid (VRLA), Battery recharge time: 3 h. Form factor: Rackmount/Tower, Product colour: Black, Housing material: Metal. Width: 433 mm, Depth: 500 mm, Height: 86.5 mm



Features		Battery	
UPS topology *	Line-Interactive	Battery technology	Sealed Lead Acid (VRLA)
Output power capacity *	3 kVA	Number of batteries supported	1
Output power *	3000 W	Battery recharge time	3 h
Waveform *	Pure sine	Hot-swap battery	✓
Input operation voltage (min) *	200 V	Design	
Input operation voltage (max) *	240 V	Form factor *	Rackmount/Tower
Input frequency *	50/60 Hz	Housing material	Metal
Output operation voltage (min)	220 V	Rack capacity	2U
Output operation voltage (max)	240 V	Extended battery module rack capacity	2U
Output frequency	50/60 Hz	Cable length	3.05 m
Automatic Voltage Regulation (AVR)	✓	Cooling type	Active
Maximum current	16 A	Built-in fan	✓
Surge energy rating	2430 J	Product colour *	Black
Response time	6 ms	Control type	Buttons
Heat dissipation	96.7 BTU/h	Display type	LCD
Number of input phases	1	LED indicators	✓
Number of output phases	1	Operational conditions	
Output power factor	1	Operating temperature (T-T)	0 - 40 °C
Power Factor Correction (PFC) type	Active	Storage temperature (T-T)	-15 - 45 °C
Emergency Power Off (EPO)	✓	Operating relative humidity (H-H)	0 - 95%
EMI/RFI noise filtering	✓	Storage relative humidity (H-H)	0 - 95%
Surge protection	✓	Operating altitude	0 - 3000 m
Power protection features	Overload	Non-operating altitude	0 - 15000 m
Audible alarm modes	Alarm when on battery, Fault, Low battery alarm, Overload alarm	Technical details	
Power source type	AC	Sustainability compliance	✓
Detachable power cord	✓	Compliance certificates	CE, Federal Communications Commission (FCC), RCM, RoHS, UL, VCCI
Country of origin	China	Packaging content	
Ports & interfaces		Batteries included	✓
AC outlet types	C13 coupler		
Power plug	C14 coupler		
AC outlets quantity	10 AC outlet(s)		
USB port	✓		

Ports & interfaces		Weight & dimensions	
USB 2.0 ports quantity	1	Width	433 mm
USB port type	USB Type-B	Depth	500 mm
Serial interface	✓	Height	86.5 mm
Serial interface type	RS-232	Weight	32 kg
Serial ports quantity	2	Package width	560 mm
RS-232 ports	2	Package depth	620 mm
Ethernet LAN (RJ-45) ports	2	Package height	275 mm
Emergency Power Off (EPO) connector	✓	Package weight	38.8 kg
		Package type	Box
Packaging data			
		Rack mount kit	✓
		Cables included	Serial
		Manual	✓
Other features			
		Battery type	RBP0128

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 20-OCT-2024. Prints or copies of Information are only valid on the printed Publication date