



Mid to Large Meeting Room Laser Projector with Excellent ROI

FEATURES

- DLP® technology for vibrant and rich picture quality
- Impressive 9,000 ANSI lumens of brightness, WUXGA resolution, and 20,000:1 contrast ratio for clear, crisp and bright projection
- Long lasting laser light source for constant brightness level and color performance for up to 20,000 hours operations
- Exquisitely vivid colors and natural picture with Rec. 709 color space capacity and HDR support
- Robustic operations thanks to its advanced thermal cooling technology and sealed optical engine
- Installation flexibility is ensured with 7 optional lenses and easy image adjustment
- Loud and clear sound delivered by built-in 2x10W speakers
- Simple one-cable connection thanks to HDBaseT with up to 4K-UHD signal support
- DICOM Simulation Mode for medical training and seminars
- Full compatibility with NovoConnect Solution for wireless presentation and collaboration



Powerful laser projector for corporate

A smart choice for mid to large corporate meeting rooms thanks to its low total cost of ownership, the DU7295Z laser projector packs tremendous value for companies seeking maintenance-free durability up to 20,000 hours with easy installation and management. DU7295Z ensures superior visibility with 9,000 ANSI lumen brightness and vibrant true-to-life colors with Rec. 709 color space, along with exceptionally quiet 33dB operation. Furthermore, the DU7295Z can be complemented with Vivitek's NovoConnect Solution for wireless presentation and collaboration.



DU7295Z

SPECIFICATIONS

Image	Display Type	Single chip DLP® Technology by Texas Instruments
	Brightness	9000 ANSI Lumens
	Native Resolution	WUXGA (1920 x 1200)
	Max. Supported Resolution	4K-UHD (3840 x 2160) @60Hz
	Contrast Ratio	20,000:1
	Native Aspect Ratio	16:10
	Keystone Correction	Vertical +/-30°; Horizontal +/-25°
Optical	Throw Ratio	7 optional lenses from 0.78:1 to 3.0-5.0:1 throw ratio range
	Zoom Ratio	Manual Zoom & Focus
	Offset	Manual Lens Shift
	Lens Shift Range	Manual; Vertical +55%, -15%; Horizontal +/-5%
Features	Features	3D Features, 3D Ready(DLP link, PC+Video), Direct 3D (HDMI 1.4a), 3D Mandatory Formats supported (top/bottom, right/left, frame sequential), Keypad lock
Compatibility	Video	SDTV (480i, 576i) / EDTV (480p, 576p) / HDTV (720p, 1080i, 1080p), NTSC (M, 3.58/4.43 MHz), PAL (B,D,G,H,I,M,N) SECAM (B,D,G,K,K1,L), 4K-UHD
Connectivity	I/O Connection Ports	VGA-In (15pin D-Sub), HDMI Number of Ports v.2.0 (x2), DVI-D, Component (5 BNC) (RGBHV), Composite Video, Audio-In (RCA), Audio-In (Mini-Jack), VGA-Out (15pin D-Sub), Audio-Out (RCA), RJ45 (x2: LANx1, HDBaseTx1), RS-232 (x2: In and Out), 3D-Sync (x2: In and Out), USB A (Power Only), USB B (Service), Remote Jack(wire remote)
General	Lamp Life and Type	Lamp free design. Laser light source lasts up to 20,000 hours
	Dimensions (W x D x H)	470 x 517 x 202 mm
	Weight	25 kg
	Noise Level	40dB/36dB (Normal/Eco. Mode)
	Warranty	Large Venue Laser Phosphor Warranty: 5 Year projector / 5 years or 20.000h on the Laser Phosphor illumination source.(Whichever comes first)
	Standard Accessories	VGA Cable, Lens Cap, Quick Start Guide, Warranty Card (by region), Remote Controller (with battery), AC Power Cord
	Optional Accessories	Remote Control P/N (5041846600)
	UPC Code	DU7295Z-WH: 813097024459; DU7295Z-BK: 813097024541

OPTIONAL LENSES

Lens Name	Short Throw	Semi Short Throw	Standard Lens	Wide Fix	Wide Zoom	Long Zoom 1	Long Zoom 2
Aspect Ratio	16:10	16:10	16:10	16:10	16:10	16:10	16:10
Throw Ratio	1.10 - 1.30:1	1.25 - 1.60:1	1.54 - 1.93:1	0.78:1	0.77 - 1.10:1	1.93 - 2.89:1	3.00 - 5.01:1
Projection Distance	1-9	1.3-8	1.5-7	0.8-5	1-5	2-20	3-20
Image Size	36-379	39-300	37-211	48-298	43-300	33-481	28-309
Zoom	1.18	1.28	1.25	1	1.42	2.5 - 3.1	1.67
F Number	2.05 - 2.27	2.0 - 2.44	2.0 - 2.09	2.5	2.1 - 2.6	28.5 - 42.75 mm	2.2 - 2.5
Focal Length	16.64 - 19.54 mm	18.65 - 23.85 mm	22.8 - 28.5 mm	11.46 mm	11.45 - 16.32 mm	44.5 - 74.19 mm	44.5 - 74.19 mm
Part Number	5811120054-SVV (VL907G/LNS-5STZ)	5811122743-SVV (VL912G/LNS-5SZ12)	5811120865-SVV (VL906G/LNS-7SZ1)	5811120818-SVV (VL904G/LNS-5FX2)	5811122742-SVV (VL911G/LNS-5WZ2)	5811119237-SVV (VL908G/LNS-7LZ1)	5811120055-SVV (LNS-5LZ2)