## TP-Link TL-SG1218MP commutateur réseau Non-géré Gigabit Ethernet (10/100/1000) Connexion Ethernet, supportant l'alimentation via ce port (PoE) 1U Noir

Marque : TP-Link

Code produit: TL-SG1218MP

HAR HAR


Nom du produit : TL-SG1218MP

TP-Link TL-SG1218MP. Type de commutateur: Non-géré. Type de port Ethernet RJ-45 de commutation de base: Gigabit Ethernet (10/100/1000), Quantité de ports Ethernet RJ-45 de commutation de base: 18. Full duplex. Répertoire MAC: 8000 entrées, Capacité de commutation: 36 Gbit/s. Standards réseau: IEEE 802.1Q, IEEE 802.1p, IEEE 802.3, IEEE 802.3ab, IEEE 802.3u, IEEE 802.3x. Connexion Ethernet, supportant l'alimentation via ce port (PoE). Grille de montage, Elément de format: 1U


| Management features                                |   | Design   |   |
|--|---|--|---|
| Switch type *                                      | Unmanaged   | Number of fans   | 2 fan(s)  |
| Quality of Service (QoS) support                   | 1   | Power  |   |
| Traffic classification                             | 1   | Power source *   | AC  |
| Ports & interfaces                                 |   | Power supply included *  | 1   |
| Basic switching RJ-45 Ethernet ports<br>quantity * | 18  | AC input voltage<br>AC input frequency                         | 100 - 240 V<br>50 - 60 Hz   |
| Basic switching RJ-45 Ethernet ports type *        | Gigabit Ethernet (10/100/1000)  | Power consumption (max)  | 286.64 W  |
| Gigabit Ethernet (copper) ports                    | 18  | Power over Ethernet (PoE)                                      |   |
| quantity   |   | Power over Ethernet (PoE) *                                    | <ul> <li>Image: A set of the set of the</li></ul> |
| Combo SFP ports quantity                           | 2   | Power over Ethernet plus (PoE+)                                | 16  |
| Network  |   | ports quantity<br>Power over Ethernet (PoE) power              |   |
| Networking standards *                             | IEEE 802.1Q, IEEE 802.1p, IEEE<br>802.3, IEEE 802.3ab, IEEE 802.3u,<br>IEEE 802.3x  | per port<br>Total Power over Ethernet (PoE)<br>budget          | 30 W<br>250 W   |
| 10G support *                                      | ×   | 5  |   |
| Cable types supported                              | Cat3, Cat4, Cat5, Cat5e, Cat6   | Operational conditions   |   |
| Full duplex  | 1   | Operating temperature (T-T)                                    | 0 - 50 °C   |
| Half duplex  | 1   | Storage temperature (T-T)<br>Operating relative humidity (H-H) | -40 - 70 °C<br>10 - 90%   |
| Flow control support                               | 1   | Storage relative humidity (H-H)                                | 5 - 90%   |
| Auto MDI/MDI-X                                     | 1   | Heat dissipation   | 977.44 BTU/h  |
| Ethernet LAN data rates                            | 10,100,1000 Mbit/s  | Weight & dimensions  |   |
| Auto-negotiation                                   | 1   | Width  | 440 mm  |
| MAC address auto-learning<br>supported             | <ul> <li>Image: A start of the start of</li></ul> | Depth  | 180 mm  |
| MAC address auto-aging supported                   | 1   | Height   | 44 mm   |
| Data transmission                                  |   | Packaging content  |   |
| Switching capacity *                               | 36 Gbit/s   | Cables included  | AC  |

Publication date: 01-MAR-2025. Prints or copies of Information are only valid on the printed Publication date


| Data transmission                           |                                      | Packaging content                                |                           |
|---|--------------------------------------|--|---------------------------|
| orwarding rate 26.78 Mpps                   | Quick start guide                    | ✓  |                           |
| MAC address table *<br>Jumbo frames support | 8000 entries<br>✓<br>10000<br>4.1 MB | Packaging data                                   |                           |
| Jumbo frames<br>Packet buffer memory        |                                      | Package width<br>Package depth<br>Package height | 250 mm<br>528 mm<br>80 mm |
| Design                                      |                                      | Package weight                                   | 3.05 kg                   |
| Rack mounting *                             | ✓                                    | Certificates                                     |                           |
| Form factor<br>Product colour               | 1U<br>Black                          | Certification                                    | CE, FCC, RoHS             |
| Housing material                            |                                      | Logistics data                                   |                           |
| LED indicators                              | 1                                    | Harmonized System (HS) code                      | 85176990                  |













Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.