Yealink

# Yealink W90DM station de base DECT Blanc

**Marque :** Yealink

**Code produit:** 1302016

**Nom du produit :** W90DM

Yealink W90DM. Protocoles de gestion: TFTP/FTP/HTTP/HTTPS/RPS, Protocoles réseau pris en charge: SIP v1 (RFC2543), v2 (RFC3261), SNTP/NTP, VLAN (802.1Q and 802.1P), 802.1x, LLDP, STUN, UDP/TCP/TLS, Algorithme de sécurité soutenu: AES, HTTPS, SHA-384, SHA-512, SRTP, TLS. Phonebook capacity (per handset): 100 entrées. Frequency range (EU): 1880 - 1900 MHz, Frequency range (US): 1920 - 1930 MHz, Gamme intérieure maximale: 50 m. Ethernet LAN data rate supported (max): 100 Mbit/s. Couleur du produit: Blanc

## Performance

| | |
|---|---|
| Number of handsets supported (max) * | 250 |
| Number of carrier frequencies | 2 |
| Number of VoIP accounts | 250 |
| Management protocols | TFTP/FTP/HTTP/HTTPS/RPS |
| Supported network protocols | SIP v1 (RFC2543), v2 (RFC3261), SNTP/NTP, VLAN (802.1Q and 802.1P), 802.1x, LLDP, STUN, UDP/TCP/TLS |
| Number of bases supported (max) | 60 |
| Security algorithms | AES, HTTPS, SHA-384, SHA-512, SRTP, TLS |
| Wireless synchronization | ✔ |
| Hearing aid compatibility | ✔ |
| Dual-Tone Multi-Frequency (DTMF) | ✔ |
| Keypad lock | ✔ |
| XML browser | ✔ |
| IPUI registration | ✔ |
| User access level | ✔ |
| Auto-provision | ✔ |
| Over the Air Updates (OTA) | ✔ |

## Call management

| | |
|---|---|
| Conference call | ✔ |
| Number of parallel conferences | 3 |
| Phonebook capacity (per handset) | 100 entries |
| Number of simultaneous calls (max) | 100 |
| Number of WB calls per base supported (max) | 8 |
| Number of NB calls per base supported (max) | 8 |
| Number of simultaneous calls per handset | 2 |
| Anonymous call | ✔ |
| Anonymous call rejection | ✔ |
| Call waiting | ✔ |
| Call forwarding | ✔ |
| Caller ID | ✔ |
| Remote phonebook | ✔ |
| Call transfer | ✔ |
| Call hold | ✔ |
| Do not disturb function | ✔ |
| Switching between calls | ✔ |
| Mute function | ✔ |

## Call management

| | |
|---|---|
| Integrated voicemail | ✔ |
| Redialing | ✔ |
| Message Waiting Indication (MWI) function | ✔ |
| Phonebook search/import/export function | ✔ |
| Call history | ✔ |
| Reset function | ✔ |
| Emergency call | ✔ |
| Shared Call Appearance (SCA) | ✔ |
| System log export | ✔ |

## Antenna

| | |
|---|---|
| Frequency range (EU) | 1880 - 1900 MHz |
| Frequency range (US) | 1920 - 1930 MHz |
| Maximum indoor range | 50 m |
| Maximum outdoor range | 300 m |

## Ports & interfaces

| | |
|---|---|
| Ethernet LAN | ✔ |
| Ethernet LAN (RJ-45) ports | 1 |
| Ethernet LAN data rate supported (max) | 100 Mbit/s |

## Design

| | |
|---|---|
| Product colour | White |
| Full duplex | ✔ |
| Wall mountable | ✔ |
| LED indicators | ✔ |

## Power

| | |
|---|---|
| Input voltage | 100 - 240 V |
| Power over Ethernet (PoE) | ✔ |
| Output voltage | 5 V |
| Output current | 1.2 A |

## Operational conditions

| | |
|---|---|
| Operating temperature (T-T) | 0 - 40 °C |
| Operating relative humidity (H-H) | 10 - 95% |

## Weight & dimensions

| | |
|---|---|
| Dimensions (WxDxH) | 134 x 100 x 28 mm |
| Weight | 2.8 kg |
| Package width | 158 mm |
| Package depth | 203 mm |
| Package height | 63 mm |
| Package weight | 3.4 kg |

| Call management | | | Logistics data | |
|---|---|---|---|---|
| Speed dialling | ✔ | | Harmonized System (HS) code | 85177900 |
| | | | **Packaging content** | |
| | | | Quick start guide | ✔ |

6938818306202