



LED DISPLAY

TD1630-3

Key Features

- HD 768p resolutie
- 10-point capacitive touch
- HDMI en VGA inputs
- 2 ingebouwde speakers
- Duurzaam, krasbestendig scherm



Product Description

De ViewSonic TD1630-3 is een 16-inch (15,6-inch zichtbaar) scherm met 10-punts multi-touch functionaliteit. Met een geavanceerd ergonomisch ontwerp kan de TD1630-3 kantelen of plat liggen om gebruikers maximaal comfort te bieden. Dit scherm biedt veelzijdigheid aan touchscreen en biedt fantastische flexibiliteit voor winkel- of zakelijke instellingen, waarbij VGA- en HDMI-ingangen voldoende connectiviteit bieden. Compatibiliteit met een breed scala aan besturingssystemen, waaronder Windows 10- en Linux-versies *, samen met dubbele geïntegreerde luidsprekers, maken van dit intuïtieve touchscreen een zeer nauwkeurige, ultra-responsieve touch-ervaring die ideaal is voor interactiviteit in winkels of bedrijven. *Ondersteunt Windows 7/8/10, Linux Kernel 4.X/3.X



1. Internal Speakers
2. USB
3. DC In
4. VESA Compatible(Wall Mount 75x75mm)
5. VGA
6. HDMI

7. Earphone

Visit Us - www.viewsonic.com

DISPLAY

Monitor Size:	16"W (15.6" Viewable)
Panel Technology:	TN TFT LCD
Resolution:	HD 1366 x 768
Display Area:	344.23mm (H) x 193.54mm (V)
Aspect Ratio:	16:9
Brightness:	220 cd/m ² (Typ) w/o touch module, 190 cd/m ² (Typ) w/ touch module
Contrast Ratio:	500:1 (Typ)
Dynamic Contrast Ratio:	10,000,000:1
Viewing Angles:	90 graden / 60 graden (Typ)
Response Time:	12ms
Colours:	262K kleuren (6-bit)
Colour Gamut:	45% of NTSC (Typ)
Panel Surface:	≥7H, Haze < 2%

INPUT SIGNAL

Frequency:	Fh = 30 ~ 61KHz ; Fv = 56 ~ 75Hz
Sync:	Separate Sync, TMDS

COMPATIBILITY

PC:	Windows 7/8/10 getest
Mac®:	Display: Power Mac getest, Touch Module:iOS not support

CONNECTOR

Input:	VGA x 1 HDMI x 1 (v1.4 compatible) Audio in x1 (3.5mm plug)
--------	---

AUDIO

Speaker:	1W x 2
----------	--------

USB

Upstream:	Type B x 1
-----------	------------

POWER

Power:	5.5 x 2.1 x 11 mm DC connector
Voltage:	AC 100-240V (Universal); 50/60Hz
Consumption:	5.5W
Optimize:	4.9W
Conserve:	4.3W

ERGONOMICS

Tilt:	15 ~ 50 graden
-------	----------------

SPECIAL FEATURES

Eye Care:	Blauw licht filter
-----------	--------------------

WALL MOUNT

VESA®:	75mm x 75mm
--------	-------------

OPERATING CONDITIONS

Temperature (° F / ° C):	32°F to 104°F (0°C to 40°C)
Humidity:	20% to 85% (niet condenserend)

DIMENSIONS (W X H X D) (MM)

Physical with stand (mm):	379.24mm (W) x 247.12mm (H) x 37.15mm (D) (@0 degree)
Physical without stand (mm):	379.24mm (W) x 247.12mm (H) x 37.15mm (D)
Packaging (mm):	453mm (W) x 389mm (H) x 86mm (D)

WEIGHT

Net with stand:	1.32kg
Net without stand:	1.32kg
Gross:	2.5kg

REGULATIONS

VSI:	CE, CE EMC, CB, RoHS, ErP, REACH, WEEE, EAC, UkrSEPRO, RCM, GEMS, BIS
------	---

WARRANTY

*Warranty offered may differ from market to market

PACKAGE CONTENTS

LCD Display 40W AC/DC Adapter (1.2m) Power Cable (1.5m) VGA Cable (1.5m) USB2.0 Cable (1.8m) Audio Cable (1.8m) Quick Start Guide
