SAMSUNG

Samsung LH98QMCEBGCXEN Signage Display Digitale signage flatscreen 2,49 m (98") LED Wi-Fi 500 cd/m² 4K Ultra HD Zwart Tizen 7.0 24/7

Merk : Samsung

Artikelcode: LH98QMCEBGCXEN

Productnaam : LH98QMCEBGCXEN

Samsung LH98QMCEBGCXEN. Product design: Digitale signage flatscreen. Beeldschermdiagonaal: 2,49 m (98"), Display technologie: LED, Resolutie: 3840 x 2160 Pixels, Helderheid: 500 cd/m², HD type: 4K Ultra HD. Wi-Fi. Operating hours (hours/days): 24/7. Inclusief besturingssysteem: Tizen 7.0. Kleur van het product: Zwart





Display		Design	
Panel typeVADisplay diagonal *2.49 m (98")Display technology *LEDDisplay resolution *3840 x 2160 pixelsDisplay brightness *500 cd/m²HD type *4K Ultra HD	2.49 m (98") LED 3840 x 2160 pixels 500 cd/m²	Product design * Product colour * VESA mounting * Panel mounting interface Performance	Digital signage flat panel Black ✓ 600 x 400 mm
Touchscreen * Native aspect ratio Response time Contrast ratio (typical)	chscreen *×ive aspect ratio16:9ponse time8 mstrast ratio (typical)5500:1namic contrast ratio marketing neMega Contrastving angle, horizontal178°wing angle, vertical178°	Purpose * Operating hours (hours/days) HDCP HDCP version	Universal 24/7 ✓ 2.2
Dynamic contrast ratio marketing name Viewing angle, horizontal Viewing angle, vertical Pixel pitch		Power Power consumption (typical) * Power consumption (standby) * Input voltage	363 W 0.5 W 100-240 V
Protein price0.562 x 0.562 mmColour saturation25%Horizontal scan range30 - 81 kHzVertical scan range48 - 75 Hz	Computer system Internal memory Operating system installed	16 GB Tizen 7.0	
Ports & interfaces		Weight & dimensions	
HDMI ports quantity *3HDMI version2.0DisplayPorts quantity *1DisplayPorts in1	2.0 1	Display width Display depth Display height Display weight	2193.2 mm 48.1 mm 1248.8 mm 56.3 kg
DisplayPort version	1.2	Packaging data	
USB port * USB ports quantity 2 Ethernet LAN * Wi-Fi * V	Package width Package depth Package height Package weight	2370 mm 230 mm 1395 mm 77.2 kg	
Audio		Operational conditions	
Built-in speaker(s) *	1	Operating temperature (T-T) Operating relative humidity (H-H)	0 - 40 °C 10 - 80%



8806095638416

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.